


T. 133 R. 31 M. 5TH Coordinates: X _____ Y _____
NE 21 Corner common to sections 15, 16, 21, 22



○ = Corner

EXISTING SURVEYS

| Original Government Survey | | | |
|----------------------------|---------------|----------------|---------------|
| Year surveyed | <u>1863</u> | | |
| Original monument | <u>Post</u> | | |
| Species | Bearing | Trees | |
| <u>PINE</u> | <u>ASPEN</u> | <u>ASPEN</u> | <u>PINE</u> |
| Diameter | <u>4"</u> | <u>10"</u> | <u>4"</u> |
| Bearing | <u>N 86 E</u> | <u>S 85 W</u> | <u>S 37 E</u> |
| Distance | <u>91 LKS</u> | <u>170 LKS</u> | <u>70 LKS</u> |

| Original Evidence Found | |
|------------------------------|----------|
| Year of search | By _____ |
| Monument found | _____ |
| Original Bearing Trees Found | |
| Species | _____ |
| Diameter | _____ |
| Bearing | _____ |
| Distance | _____ |

| Subsequent Corner Restoration | |
|-------------------------------|-----------------------------------|
| Year surveyed | <u>1915</u> By <u>E. B. Hoxst</u> |
| Location filed | <u>County Book "C" P. 87</u> |
| Monument | <u>SET LARGE WOOD POST</u> |

| Evidence of Subsequent Corner Restoration | |
|--|-------------------------------------|
| Year of search | <u>1981, 1982</u> By <u>MN/ DOT</u> |
| <u>Find 2" lip. in road, per 1915 survey, error find - set cast iron monument at true position</u> | |
| <u>Certificate - Al Welle - 1987 - Doc # 298407</u> | |

| Bearing Trees, Reference Objects | | | |
|----------------------------------|-------|-------|-------|
| Species | _____ | _____ | _____ |
| Diameter | _____ | _____ | _____ |
| Bearing | _____ | _____ | _____ |
| Distance | _____ | _____ | _____ |

| Bearing Trees, Reference Objects | | |
|----------------------------------|---------------|---------------|
| <u>3/4" lip. set</u> | <u>OAK</u> | <u>OAK</u> |
| <u>in 2" lip.</u> | <u>12"</u> | <u>12"</u> |
| <u>westerly</u> | <u>N NW</u> | <u>S SW</u> |
| <u>2 20.00'</u> | <u>48.77'</u> | <u>30.47'</u> |

| Subsequent Corner Restoration | |
|-------------------------------|--|
| Year surveyed | <u>1997</u> By <u>Nielsen #11865</u> |
| Location filed | <u>CCSO</u> |
| Monument | <u>Cert. of Survey indicates monument found.</u> |

| Evidence of Subsequent Corner Restoration Found | |
|--|-----------------------|
| Year of search | By _____ |
| <u>Certificate - Al Welle MN/ DOT - 1987 Doc. # 298407</u> | |
| <u>2000 AUG. - CCSO</u> | |
| <u>Find in place; CIM, dwn 0.2'. Located 0.5' S of E/W fence, 47'± N of & trail, and 210'± from & trail west to & Tap. Rd.</u> | |
| <u>REF. TIES:</u> | |
| <u>12" W. Oak</u> | <u>S 65° E 59.81'</u> |
| <u>16" W. Oak</u> | <u>S 51° W 30.30'</u> |
| <u>Fencepost</u> | <u>N 64° W 1.28'</u> |
| <u>Fencepost</u> | <u>N 85° E 7.75'</u> |
| <u>* dist. to dbl. hd. nail</u> | |
| <u>- corner GPS 11/4/02 CCSO</u> | |
| <u>Cim, Flash, under E/W fence</u> | |
| <u>May 1914, Tap rd order shows no survey</u> | |
| <u>Aug. 1914, Tap rd order shows no survey</u> | |