


Index No. P 9

CASS COUNTY LAND CORNER RECORD

T. 134 R. 30 M. \_\_\_\_\_ Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
E 1/4 20 Corner common to sections 20, 21



○ = Corner

EXISTING SURVEYS

**Original Government Survey**  
 Year surveyed 1868  
 Original monument Post

Species	Bearing	Trees
<u>W. PINE</u>	<u>W. PINE</u>	
Diameter <u>30"</u>	<u>28"</u>	
Bearing <u>N 6 W</u>	<u>S 38 1/4 W</u>	
Distance <u>35 LKS.</u>	<u>48 LKS.</u>	

**Original Evidence Found**  
 Year of search \_\_\_\_\_ By \_\_\_\_\_  
 Monument found \_\_\_\_\_

**Original Bearing Trees Found**

Species	Bearing	Distance
_____	_____	_____
_____	_____	_____
_____	_____	_____

**Subsequent Corner Restoration**  
 Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
 Location filed \_\_\_\_\_  
 Monument \_\_\_\_\_

**Evidence of Subsequent Corner Restoration**  
 Year of search 1987 By Dave Lundecker  
Corner Certificate - Doc # 302262  
Set cast iron monument at proportional position

**Bearing Trees, Reference Objects**

Species	Bearing	Distance
_____	_____	_____
_____	_____	_____
_____	_____	_____

**Bearing Trees, Reference Objects**

Species	Bearing	Distance
<u>Red maple</u>	<u>Red oak</u>	<u>Red oak</u>
<u>4"</u>	<u>12"</u>	<u>10"</u>
<u>N 30 E</u>	<u>NORTH</u>	<u>N 27 W</u>
<u>43.12'</u>	<u>59.87'</u>	<u>30.28'</u>
		<u>Red oak</u>
		<u>10"</u>
		<u>S 80 W</u>
		<u>40.68'</u>

**Subsequent Corner Restoration**  
 Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
 Location filed \_\_\_\_\_  
 Monument \_\_\_\_\_

**Evidence of Subsequent Corner Restoration Found**  
 Year of search \_\_\_\_\_ By \_\_\_\_\_  
Certificate - Dave Lundecker - 1987  
Doc. # 302262

Re monumentation certificate prepared \_\_\_\_\_ By \_\_\_\_\_  
 Filed at \_\_\_\_\_ Date \_\_\_\_\_