


Index No. A 15

CASS COUNTY LAND CORNER RECORD

T. 134 R. 32 M. 5TH Coordinates: X _____ Y _____
N¹/₄ 3 Corner common to sections 3 AND 34-136-32



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1858

Original monument POST

Species	Bearing	Trees
<u>SP. PINE</u>	<u>SP. PINE</u>	
Diameter <u>12"</u>	<u>10"</u>	
Bearing <u>S 89 1/2 E</u>	<u>N 88 W</u>	
Distance <u>482 LKS</u>	<u>519 LKS</u>	

Original Evidence Found

Year of search _____ By _____

Monument found _____

Original Bearing Trees Found

Species	Bearing	Distance
_____	_____	_____
_____	_____	_____
_____	_____	_____

Subsequent Corner Restoration

Year surveyed _____ By _____

Location filed _____

Monument _____

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Evidence of Subsequent Corner Restoration

Year of search 1985, 1986 By Surveyors office

9/19/85 - dug at proportional point provided by Camstock & Davis dug 11' E-W X 9' N-S X 5' deep. 6" top sand & gravel 2.5' Fill 1' rest dug 1 into nature)

Sandy - learn - nothing

8/25/86 - set cast iron at proportional point

Bearing Trees, Reference Objects

<u>Poplar</u>	<u>E. end by dge</u>
<u>5"</u>	<u>60 d spike</u>
<u>S 55° W</u>	<u>S 78° W</u>
<u>54.56'</u>	<u>56.52'</u>

Certificate - Curt - 1987 - Doc # 297516

Subsequent Corner Restoration

Year surveyed _____ By _____

Location filed _____

Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Certificate - Walt Curt - 1987

Doc. # 297516

Remuneration certificate prepared _____ By _____
Filed at _____ Date _____