


T. 135 R. 29 M. 5TH Coordinates: X _____ Y _____
E 1/4 S _____ Corner common to sections 4, 5



EXISTING SURVEYS

Original Government Survey

Year surveyed 1865
Original monument POST

Original Evidence Found

Year of search _____ By _____
Monument found _____

Species	Bearing	Trees
<u>N. PINE</u>	<u>W. PINE</u>	
Diameter <u>30"</u>	<u>10"</u>	
Bearing <u>N39W</u>	<u>N70E</u>	
Distance <u>9 LKS</u>	<u>27 LKS.</u>	

Original Bearing Trees Found

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1941 By JOHN Curo
Location filed COUNTY SURVEY RECORD BOOK D PR 264-265
Monument SET 3X3X15 OAK POST IN STONE ALE

Evidence of Subsequent Corner Restoration

Year of search 1969 By R.F. SCHNEIDER
PIPE - TIES: 18" N. PINE STUMP N42-15W
61.35', 14" BR. OAK 549-17W 23.50', 12" BR. OAK
568E 16.22'

1917 - Curo - micro-film - roll 1105 BK 56 P. 112. Find
NW B.T. Stump set 3X3X15" oak hub

Oct. 1903, with Hallett, Turpid order shows survey
Bearing Trees, Reference Objects

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
<u>N. Pine</u>	<u>10"</u>	<u>N42-15W</u>	<u>62.06'</u>
<u>BR. OAK</u>	<u>8"</u>	<u>549-17W</u>	<u>23.78'</u>
<u>BR. OAK</u>	<u>7"</u>	<u>568E</u>	<u>15.85'</u>
<u>Br. oak Poplar</u>	<u>6"</u>	<u>N3E</u>	<u>36.95'</u>
		<u>N80-30W</u>	<u>47.75'</u>

1941 ties → 1917 ties

Subsequent Corner Restoration

Year surveyed 4/10/84 By Freeman - Marcus
Location filed Survey Tech - Forester
Monument End 1 1/2" l.p. Flush - w/ 1 1/2" l.p. up 3'
for guard stake South of Corner 0.2'

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
PLAT - CLARK'S ADDITION
R.F. SCHNEIDER 1969
PLAT - GLIMS DALE'S GULLESTATES
DEAN ANDERSON 1973
1999 - Landecker + Assoc.
Cert. of Survey indicates monument
found.

13" N. Pine N22°W 28.00' - CCLD Tag
16" Roak 55°W 23.61' - 1941 tie
17" Roak N55°E 17.61'
- also dead Roak 568°E 16.22'