


Index No. A 25

CASS COUNTY LAND CORNER RECORD

T. 135 R. 31 M. 5TH Coordinates: X 486,734.92 Y 241,204.52
NE 1 Corner common to sections 1 AND 36-136-31 AND 31-136-30
 And 6-135-30



○ = Corner

EXISTING SURVEYS

Original Government Survey
 Year surveyed 1858 Post
 Original monument _____
 Species MAPLE BL. OAK BL. OAK LINDEN
 Diameter 12" 16" 14" 14"
 Bearing N38E S23E N55W S75W
 Distance 24LKS 41LKS 56LKS 14LKS

Original Evidence Found
 Year of search _____ By _____
 Monument found _____
 Original Bearing Trees Found
 Species _____
 Diameter _____
 Bearing _____
 Distance _____

Subsequent Corner Restoration
 Year surveyed 1915 By JOHN CURD
 Location filed COUNTY SURVEY RECORD BOOK "B" P57-61
 Monument FIND ALL 4 OLD GOUT B.T STUMPS.
SET 1x36" IRON STAKE

Evidence of Subsequent Corner Restoration
 Year of search 4/9/98 By J. WALKER MN DNR
3/4" x 24" IN 1/2" IRON PIPE WITH MN DNR SURVEY MARKER CAP

also on microfilm - roll 115 BK 94 P. 131

June 1913, Typ Road order shows no survey

Bearing Trees, Reference Objects
 Species W. OAK R. OAK SNAG OAK STUMP
 Diameter 3" 14" 16"
 Bearing S27-56E S71-30W N63-26E
 Distance 182.25' 91.70' 60.09'

Bearing Trees, Reference Objects
 Species BIRCH CENTER TEL. JCT
 Diameter 3" FE. POST POST BRACE
 Bearing N22°E S48°E S40°W
 Distance 77.95 50.43 47.72
DNR RP DNR RP DNR RP

A-25

Subsequent Corner Restoration
 Year surveyed _____ By _____
 Location filed _____
 Monument _____

Evidence of Subsequent Corner Restoration Found
 Year of search _____ By _____
May 2002 D. Leadbetter
cert of SUR shows new found
- corner GPS 10/2/02 cuso
3/4" PIN, on E 45th, 3' ± S. of
E 72nd, down 0.2.
January 1922
Typ Road order shows no survey
August 1915 - Typ Road Order shows no survey

Remonumentation certificate prepared 5/31/01
 Filed at Cass Co. Recorder # 441835

By J. Walker
 Date _____