


Index No. N 25

CASS COUNTY LAND CORNER RECORD

T. 135 R. 31 M. 5th Coordinates: X 486,754.70 Y 225,263.99
NE 24 Corner common to sections 13, 24 AND 18, 19-135-30



EXISTING SURVEYS

Original Government Survey
Year surveyed 1858
Original monument Post

Original Evidence Found
Year of search _____ By _____
Monument found _____

Species	Bearing Trees			
	MAPLE	ELM	PINE	PINE
Diameter	10"	16"	30"	36"
Bearing	SRSE	N7E	S81W	N70W
Distance	10 LKS.	28 LKS.	67 LKS.	75 LKS.

Original Bearing Trees Found

Species	Bearing	Trees	Found
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

O = Corner

Subsequent Corner Restoration
Year surveyed 1920 By LINCOLN MACKAY
Location filed County Book C P. 373
Monument END 2 W. PINE BIT STAMPS, ALSO NE AND SE BITS. AND PIECES OF ORIG. POST SET IRON MONUMENT 1923 - JOHN GREENE - MICRO FILM - ROLL 115 BK 94 P. 153 END I.M. (run from N to this corner)

Evidence of Subsequent Corner Restoration
Year of search 1973 By Don Coulter
Twp File
Found 2" 1IP.
June 1913; Twp rd order shows no survey

Bearing Trees, Reference Objects

Species	APLAR	OAK	Aspr
Diameter	7"	12"	6"
Bearing	N1-24W	S33-30E	N59-56W
Distance	29.5'	135.5'	53'

1920 trees

Bearing Trees, Reference Objects

R. oak	R. oak	R. oak	R. oak
12"	10"	12"	12"
N66-30E	N30-45E	N15-15W	S14-00W
53.30'	25.35'	13.85'	35.24'

N-25 Subsequent Corner Restoration
Year surveyed 1994 11/20 By T. Freeman D. Marcum
Location filed _____
Monument End 2" 1IP. up 0.4' and all 4 1973 B.T.S
CCLD tag on 14" R. oak N15-15W 13.85'
7/98 DNR found 2" 1IP, up 0.5', in woods, 55't W. of logging trail. Witnessed as follows:
16" Oak N15°W, 13.99'*
14" Oak N30°E, 25.57'*
20" Oak S15°W, 35.10'*
*distance to DNR RP

Evidence of Subsequent Corner Restoration Found
Year of search Oct. 1903 By W.H. Hallett
Twp rd order shows survey

Remuneration certificate prepared 5/31/01
Filed at Cass Co Recorder #441847

By J. Walker
Date _____