


Index No. J 13

CASS COUNTY LAND CORNER RECORD

T. 135 R. 32 M. 5TH Coordinates: X _____ Y _____

NE 16 Corner common to sections 9, 10, 15, 16



EXISTING SURVEYS

Original Government Survey
 Year surveyed 1866
 Original monument POST

Original Evidence Found
 Year of search _____ By _____
 Monument found _____

	Bearing Trees			
Species	<u>BL. PINE</u>	<u>BL. PINE</u>	<u>BL. PINE</u>	<u>BL. PINE</u>
Diameter	<u>8"</u>	<u>8"</u>	<u>8"</u>	<u>8"</u>
Bearing	<u>S 19 1/2 E</u>	<u>S 63 W</u>	<u>N 76 W</u>	<u>N 18 E</u>
Distance	<u>16"</u>	<u>19"</u>	<u>5"</u>	<u>19"</u>

	Original Bearing Trees Found			
Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

Subsequent Corner Restoration
 Year surveyed 1985 11/14 By Walt Curo
 Location filed Corner Certificate - Doc # 286244
 Monument End 1/2" 1/2" bent - replaced with
cast iron monument, use 8/30/1985 trees
shown below, right

Evidence of Subsequent Corner Restoration
 Year of search 1985 8/30 By Terry Freeman, Don Marcum
End 1 1/2" 1/2" 1/2" Flush, top 1 1/2" bent East
& R & E, trail N & W

CERTIFICATE BY WALT CURO, 1985, Doc # 286244

Bearing Trees, Reference Objects

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Bearing Trees, Reference Objects

J. Pine	<u>J. Pine</u>	<u>J. Pine</u>
9"	<u>7"</u>	<u>8"</u>
<u>S 52 W</u>	<u>N 48 W</u>	<u>N 8 E</u>
<u>44.63'</u>	<u>47.71'</u>	<u>58.68'</u>

Subsequent Corner Restoration
 Year surveyed 5/3/2000 By J. Walker MN/DNR
 Location filed _____
 Monument FOUND CIM & R & E - W - N

Evidence of Subsequent Corner Restoration Found
 Year of search _____ By _____
Certificate - Walt Curo - 1985 Doc # 286244

<u>DNR RD 4" OAK</u>	<u>S 30° E</u>	<u>49.48</u>
<u>FB SPK 12" J. PINE</u>	<u>N 8° E</u>	<u>58.68</u>
<u>FB SPK 14" J. PINE</u>	<u>S 50° W</u>	<u>44.63</u>

Remuneration certificate prepared _____ By _____
 Filed at _____ Date _____