


Index No. N 17

CASS COUNTY LAND CORNER RECORD

T. 135 R. 32 M. 5th Coordinates: X NE 22 Y 14, 15, 22, 23
Corner common to sections



EXISTING SURVEYS

Original Government Survey

Year surveyed 1866

Original monument Post

Species	Bearing	Trees
<u>BL. PINE</u>	<u>SPRUC</u>	<u>Y. PINE</u>
<u>14"</u>	<u>8"</u>	<u>22"</u>
<u>S26 1/2 W</u>	<u>N62 E</u>	<u>S8 E</u>
<u>113 US.</u>	<u>87 US.</u>	<u>139 US.</u>

Original Evidence Found

Year of search _____ By _____

Monument found _____

Original Bearing Trees Found

Species	Diameter	Bearing	Distance

Subsequent Corner Restoration

Year surveyed 1915 By E.B. Horst

Location filed COUNTY BOOK "C" P. 48

Monument SET 1 1/2 x 48" I.P.

1915 - R. BRYANT, Book "C" P. 572 Fnd Corner

also on microfilm roll 115 BK 71 P. 78, 85, 86

Evidence of Subsequent Corner Restoration

Year of search _____ By _____

1915 - also on microfilm - roll 115 BK 71 P. 119

P. 126-127

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
<u>J. PINE</u>	<u>8"</u>	<u>N21 E</u>	<u>85.6'</u>
<u>J. PINE</u>	<u>8"</u>	<u>S82 W</u>	<u>116'</u>
<u>J. PINE</u>	<u>10"</u>	<u>S65 E</u>	<u>67.6'</u>

1915 Horst trees

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance

N-17 Subsequent Corner Restoration

Year surveyed 3/2001 By CCSO

Location filed file #2001.023

Monument Found 1/2" pin, down 0.3'

1 1/2 S. of ♀ CR #30 and 5'± W. of

♀ CR #106. Witness as follows:

<u>Tele Ped Post</u>	<u>N 42° W, 55.59' *</u>
<u>12" Elm</u>	<u>N 44° E, 155.59' *</u>
<u>P. Pole</u>	<u>S 51° E, 55.84' *</u>
<u>E. Gate Post</u>	<u>S 48° W, 64.07' *</u>

* distance to double head nail

- Corner GPS 11/5/02 CCSO

3/8" PIN, down 0.4', on ♀ CR #30,

5' ± W of ♀ CR #106

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Remonumentation certificate prepared _____ By _____

Filed at _____ Date _____