Index No. R 7-8

CASS COUNTY LAND CORNER RECORD

T. 136 R. 29 M. 5TH Coordinates: X _____ Y _____

M.C.# 28 Corner common to sections 20,29



EXISTING SURVEYS

Original Government Survey

Year surveyed 1870

Original monument Post

Original Evidence Found

Year of search _____ By _____

Monument found _____

Bearing Trees

Species	N. Pine	N. Pine		
Diameter	10"	14"		
Bearing	S25E	N1W		
Distance	34 LKS	58 LKS		

Original Bearing Trees Found

Species				
Diameter				
Bearing				
Distance				

Subsequent Corner Restoration

Year surveyed 1909 By John Curo

Location filed County Survey Record Book 'A' P571-575

Monument Fnd old Govt B.T Stump: 14" N. Pine S25E 34 LKS.

Evidence of Subsequent Corner Restoration

Year of search 1958 By Minn DNR - Engineering

Reset Curo's Cor on line from NE Cor to E 1/16 Btw 20,29 Set I.P.

DNR 1966 - Fnd 1¼" I.P. 9.0' from waters edge

Bearing Trees, Reference Objects

Species				
Diameter				
Bearing				
Distance				

Bearing Trees, Reference Objects

Pople	N.B.C. S. Side	R. Pine 16"		
10"		N.B.C. E. Side		
East				
16.94'		22.89'		
1966		Tres		

R, 7-8

Subsequent Corner Restoration

Year surveyed 1970 By D. Andersen

Location filed

Monument No corner indicated.

1980 Landecker & Assoc found DNR iron pipe, disturbed. Set ½" pipe RLS 7452, and reset DNR pipe on Section line.

1/2003 Landecker & Assoc. found ½" pipe RLS 7452, 1½" pipe, up 1.5', 0.70' East, and witnessed:

8" J. Pine N 40° W, 10.47'
8" Ash N 43° E, 25.40'
8" Oak S 40° E, 16.75'

Certificate filed.

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Remonumentation certificate prepared ✓ By RLS #17008

Filed at CC-RO document #462470 Date 2/14/03