


Index No. L 9

CASS COUNTY LAND CORNER RECORD

T. 137 R. R9 M. 5TH Coordinates: X _____ Y _____
E 1/4 17 Corner common to sections 16, 17



EXISTING SURVEYS

Original Government Survey

Year surveyed 1865

Original monument Post

Species	Bearing	Trees
<u>BL. PINE</u>	<u>BL. PINE</u>	
<u>4"</u>	<u>4"</u>	
<u>N51E</u>	<u>S22W</u>	
<u>103 LKS</u>	<u>39 LKS.</u>	

Original Evidence Found

Year of search _____ By _____

Monument found _____

Original Bearing Trees Found

Species	Diameter	Bearing	Distance

Subsequent Corner Restoration

Year surveyed _____ By ROAD SURVEY

Location filed COUNTY BOOK 2" P474

Monument IRON MONUMENT
1914, E.A. DUNN, COUNTY BOOK "C" P564 SET HUB & JACK
SET 2x48" GALV. PIPE WITH CONCRETE

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
<u>J. PINE</u>	<u>10"</u>	<u>N28-35E</u>	<u>57.17'</u>
<u>J. PINE</u>	<u>10"</u>	<u>S74-12E</u>	<u>63.55'</u>

Evidence of Subsequent Corner Restoration

Year of search 1914 By J. CURD

Twp. Rd Order indicates Iron.

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance

L-9

Subsequent Corner Restoration

Year surveyed _____ By _____

Location filed _____

Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

CERTIFICATE - C. J. BARK - ASST HWT ENGINEER - 1922
Found 2" I.P. set in concrete by John Curd.
TIES: 2" I.P. NW 37'; 2" I.P. SW 38'; 2" I.P.
SE 46.7'

Re monumentation certificate prepared _____ By _____
Filed at _____ Date _____