


Index No. A 19

CASS COUNTY LAND CORNER RECORD

T. 137 R. 30 M. 5TH Coordinates: X _____ Y _____
N 1/4 R Corner common to sections 2 AND 35-138-30



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1865
Original monument Post

Species	Bearing	Trees
<u>Bl. Pine</u>	<u>Bl. Pine</u>	
Diameter <u>8"</u>	<u>12"</u>	
Bearing <u>N42W</u>	<u>S50W</u>	
Distance <u>4 LKS.</u>	<u>15 LKS</u>	

Original Evidence Found

Year of search _____ By _____
Monument found _____

Original Bearing Trees Found

Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration

Year surveyed 1965 By R.F. SCHNEIDER
Location filed (COUNTY BOOK 'D' P. 456)
Monument IRON PIN (NEW TIES)

Evidence of Subsequent Corner Restoration

Year of search 1999 By CCSO
Set PK from Landecker Survey info.
7.9' S. of G #2.

Bearing Trees, Reference Objects

Species			
<u>J. PINE</u>	<u>TELE. POLE</u>	<u>N. PINE</u>	
Diameter <u>12"</u>	<u>N47E</u>	<u>6"</u>	
Bearing <u>N14 1/2 E</u>	<u>36.05'</u>	<u>S52W</u>	
Distance <u>123.6'</u>		<u>53.9'</u>	

Bearing Trees, Reference Objects

<u>Balsam</u>	<u>R. Pine</u>	<u>R. Pine</u>	<u>Spruce</u>
Diameter <u>8"</u>	<u>11"</u>	<u>11"</u>	<u>4"</u>
Bearing <u>N52°E</u>	<u>S42°E</u>	<u>S24°W</u>	<u>N35°W</u>
Distance <u>107.12' *</u>	<u>60.38' *</u>	<u>36.34' *</u>	<u>67.84' *</u>

*distance to double head nail

A-19 **Subsequent Corner Restoration**

Year surveyed Sept. 2006 By J. Nielsen #11865
Location filed _____
Monument Cert of Surv. shows Mon. Found

April 2004 B. Grivna #17253
Cert of Survey shows monument found

Aug. 1904 W.H. Hallett
Trap rd order shows survey

Evidence of Subsequent Corner Restoration Found

Year of search June 2005 By J. Kramer #23668
Cert. of Survey indicates monument found

Remonumentation certificate prepared _____
Filed at _____

By _____
Date _____