


Index No. R17

CASS COUNTY LAND CORNER RECORD

T. 137 R. 30 M. 5th Coordinates: X _____ Y _____
NE 27 Corner common to sections 22, 23, 26, 27



EXISTING SURVEYS

Original Government Survey
 Year surveyed 1870
 Original monument POST

	Bearing Trees			
Species	<u>TAM.</u>	<u>TAM.</u>	<u>TAM.</u>	<u>TAM.</u>
Diameter	<u>4"</u>	<u>3"</u>	<u>5"</u>	<u>6"</u>
Bearing	<u>N32W</u>	<u>N67E</u>	<u>S78 1/2 E</u>	<u>S38W</u>
Distance	<u>5 LKS</u>	<u>8 LKS</u>	<u>15 LKS</u>	<u>4 LKS</u>

Original Evidence Found
 Year of search _____ By _____
 Monument found _____

Original Bearing Trees Found

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Subsequent Corner Restoration
 Year surveyed 1911 By A.W. Maulster
 Location filed microfilm - Roll 105 BK 49 P. 100
 Monument start S. from corner previously established by Curo
849 P. 132 - set 2x48" Iron

Evidence of Subsequent Corner Restoration
 Year of search 1908 By John Curo
microfilm - roll 115 BK 85 P. 244
Start line E from corner set previously by John Curo.

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Subsequent Corner Restoration
 Year surveyed _____ By _____
 Location filed _____
 Monument _____

Evidence of Subsequent Corner Restoration Found
 Year of search 2000 By CCSO
find incl. 8" Pole nail, down 0.4'.
Located E of 40th St. SW & E 32nd Ave SW.

REF. TIES: 7" R. Oak N 20° W 66.79'
P. Pole N 45° E 49.61' (TAG)
"X" in 14" culv. S 78° E 31.73'
P.K. in 14" CMP S 72° W 50.19'

* unless otherwise noted, distance is pulled to dbl. hd. nail.