


Index No. R 25

CASS COUNTY LAND CORNER RECORD

T. 137 R. 30 M. 5TH Coordinates: X _____ Y _____
NE 25 Corner common to sections 24, 25 AND 19, 30 - 137-29



EXISTING SURVEYS

Original Government Survey
Year surveyed 1865
Original monument POST

Original Evidence Found
Year of search _____ By _____
Monument found _____

		Bearing Trees		
Species	<u>W. PINE</u>	<u>W. PINE</u>	<u>SPRUCE</u>	<u>PINE</u>
Diameter	<u>14"</u>	<u>18"</u>	<u>15"</u>	<u>12"</u>
Bearing	<u>N65E</u>	<u>N37W</u>	<u>S33W</u>	<u>S37 1/2 E</u>
Distance	<u>68 LKS.</u>	<u>105 LKS.</u>	<u>47 LKS.</u>	<u>61 LKS.</u>

		Original Bearing Trees Found	
Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Subsequent Corner Restoration
Year surveyed 1909 By JOHN CURD
Location filed COUNTY SURVEY RECORD BOOK A" P 318-328
Monument FOUND OLD GOLF POST & 3 B.T'S SET 8x8x36"
CEMENT POST IN 1910

Evidence of Subsequent Corner Restoration
Year of search 1909 By A.W. Moulster
MICROFILM - ROLL 105 - BK 48 P 8-9
FIND NW, NE & SE B.T'S - same as Book A
1910 - CURD - microfilm - roll 115 BK 91 P. 24
begin at corner previously established - run w.
Bearing Trees, Reference Objects

		Bearing Trees, Reference Objects		
Species	<u>TACK W. PINE</u>	<u>W. PINE</u>	<u>PINE</u>	
Diameter	<u>18"</u>	<u>TACK 14"</u>	<u>12"</u>	<u>TACK</u>
Bearing	<u>N35-22W</u>	<u>N64-40E</u>	<u>S38-48E</u>	
Distance	<u>68.03'</u>	<u>44.88'</u>	<u>39.53'</u>	

Subsequent Corner Restoration R-25
Year surveyed 1914 By _____
Location filed _____
Monument C. DITCH SURVEY BK 22 BOX 3 OF
C. DITCH SURVEY BOOKS, PG 69

-Corner GPS 9/17/02 CCSO
1" ODP/W cap #17253, Flush, on E

Evidence of Subsequent Corner Restoration Found
Year of search _____ By _____

Remonumentation certificate prepared _____ By _____
Filed at _____ Date _____