


Index No. 29

CASS COUNTY LAND CORNER RECORD

T. 137 R. 30 M. 5TH Coordinates: X _____ Y _____
SE 32 Corner common to sections 32, 33



EXISTING SURVEYS

Original Government Survey
 Year surveyed 1858
 Original monument lost

Species	Bearing	Trees
<u>TAM</u>	<u>TAM</u>	
<u>4"</u>	<u>6"</u>	
<u>N 45 1/4 E</u>	<u>N 13 3/4 W</u>	
<u>5 LKS</u>	<u>37 LKS</u>	

Original Evidence Found
 Year of search _____ By _____
 Monument found _____

Original Bearing Trees Found

Species	Diameter	Bearing	Distance

Subsequent Corner Restoration
 Year surveyed 1908 By JOHN CURD
 Location filed COUNTY SURVEY RECORD BOOK B' P 140-157
 Monument TWO STAKE SET BY CAMPFIELD IN PLACE BE OLD C&T STAKE
1911, A.W. MAULSTAR BOOK B' P 258-264 SET 2x48" GALV. I.P.
SURVEY OF STATE RURAL HWY 80 BOOK B' P 474-475 2" I.P.

Bearing Trees, Reference Objects

Species	Bearing	Distance
<u>F.P.</u>	<u>F.P.</u>	<u>1908 - also on</u>
	<u>534-54W</u>	<u>microfilm - roll 115</u>
	<u>N 34 - 15 W</u>	<u>BK 85 P. 237</u>
	<u>31.85'</u>	<u>38.80'</u>
	<u>1908 ties</u>	

Evidence of Subsequent Corner Restoration
 Year of search 1977 By Rif. Schneider for Hwy Dept
CO RPT # 28
Corner position from road stationing

1911 also on microfilm - Roll 105 BK 49 P. 113
P. 133 SET 2x48" I.M.

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance

2-9

Subsequent Corner Restoration
 Year surveyed JUNE 1995 By MN DNR
 Location filed CCSO - STR FILE
 Monument FOUND 3" SQUARE MON @ RDS E, W & N
STATIC GPS OCCUPATION

Evidence of Subsequent Corner Restoration Found
 Year of search MAR. 2000 By CCSO
 Fnd. in place; 3" x 3" sq. tel spar cap
flush w/ bit. Located @ Co. Rd. 26 and
E Co. Rd. 28.

REF. TIES:

- * P. Pole N 20° E 212.63'
- * Tel. Ped. N 40° W 83.68'
- CR 28 Signpost (N. Flange) S 68° W 55.09'
- ARROW SIGN (E. Flange of E. Post) S 15° W 25.95'
- * distance pulled to db. hd. nail

- Corner GPS 9/17/02 CCSO
Alum cap, E E