


T. 138 R. 30 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
N 14 B Corner common to sections 5, 6



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1865  
Original monument POST

Species	Bearing	Trees
<u>BL. PINE</u>	<u>BL. PINE</u>	
<u>7"</u>	<u>6"</u>	
<u>N88E</u>	<u>S88E</u>	
<u>1326 LKS</u>	<u>1333 LKS.</u>	

Original Evidence Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

Original Bearing Trees Found

Species	Diameter	Bearing	Distance

Subsequent Corner Restoration

Year surveyed 1913 By JOHN CURD  
Location filed COUNTY SURVEY RECORD BOOK B P. 289-300  
Monument FIND OLD COUT BITS: 7" J. PINE N88E 1326 LKS.  
6" BL. PINE S88W 1333 LKS, SET 2x48" GALV. I.P. W/CA  
IN CONCRETE

Evidence of Subsequent Corner Restoration

Year of search 1924 By Minn. Hwt Dept.  
R/W map in Recorder's office - Lothrop to Pine  
River  
Spike & iron pipe 2621.3' to NE T

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance

Subsequent Corner Restoration E - 7

Year surveyed 1917 By John Curd  
Location filed Microf. Im - Roll 105 Coordinates BK - Cass 2  
Monument 2' 2x48" galv. I.P. P. 44

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
CERTIFICATE - R.F. SCHNEIDER - 1967  
Set 1/2" iron pipe TIES: TELE. POLE SW 51.20';  
POWER POLE SE 47.57'; TELE. POLE NNW  
184.06'.  
10/99 - Landecker & Assoc. Cert of  
Survey indicates monument found.

Remonumentation certificate prepared \_\_\_\_\_  
Filed at \_\_\_\_\_

By \_\_\_\_\_  
Date \_\_\_\_\_