


Index No. A 11

CASS COUNTY LAND CORNER RECORD

T. 138 R. 32 M. 5TH Coordinates: X Y
N 1/4 4 Corner common to sections 4 AND 33-139-32



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1860
Original monument Post

Original Evidence Found

Year of search _____ By _____
Monument found _____

Bearing Trees

Species TAM TAM
Diameter 4" 5"
Bearing S50W N13 1/2 E
Distance 152 LKS. 352 LKS.

Original Bearing Trees Found

Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration

Year of search MAY 1977 By K. DONAGHE, MN/DOT
SET 2" SQUARE STEEL TUBE WITH ALUMINUM
CAP AT LOST POSITION, UP 1.0'
CERT. OF LOCATION DOC. # 433373
48.5' S SOUTH OF TRAIL

Bearing Trees, Reference Objects

Species _____
Diameter _____
Bearing _____
Distance _____

Bearing Trees, Reference Objects

N&D 5" ASPEN N17°E 35.65
N&D 4" ASPEN S64°W 53.39
N&D 4" ASPEN S88°W 58.88
N&D 3" ASPEN N29°W 16.22
STEEL SIGN POST SOUTH 1.0

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Remonumentation certificate prepared _____

By _____

Filed at _____

Date _____