


Index No. E 13

CASS COUNTY LAND CORNER RECORD



T. 138 R. 32 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
NE 9 Corner common to sections 3, 4, 9, 10

EXISTING SURVEYS

Original Government Survey

Year surveyed 1870  
 Original monument POST

Original Evidence Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
 Monument found \_\_\_\_\_

	Bearing Trees			
Species	<u>TAM</u>	<u>TAM</u>	<u>TAM</u>	<u>TAM</u>
Diameter	<u>7"</u>	<u>7"</u>	<u>4"</u>	<u>7"</u>
Bearing	<u>S55W</u>	<u>N53 1/2 E</u>	<u>S25 1/2 E</u>	<u>N28 1/2 W</u>
Distance	<u>11 LKS.</u>	<u>15 LKS</u>	<u>6 LKS</u>	<u>9 LKS</u>

Original Bearing Trees Found

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
 Location filed \_\_\_\_\_  
 Monument \_\_\_\_\_

Evidence of Subsequent Corner Restoration

Year of search MAY 1997 By K. DONAGUE, MN/DOT  
SET ALUM. CAPPED 2" SQUARE STEEL  
TUBE MON AT LOST POSITION.  
CERT. OF LOCATION DOC. # 438377

Bearing Trees, Reference Objects

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

Bearing Trees, Reference Objects

<u>N&amp;D</u>	<u>4" ASPEN</u>	<u>S56°E</u>	<u>23.84</u>
<u>N&amp;D</u>	<u>6" ASPEN</u>	<u>S11°E</u>	<u>51.13</u>
<u>N&amp;D</u>	<u>4" ASPEN</u>	<u>S14°W</u>	<u>47.84</u>
<u>N&amp;D</u>	<u>3" ASPEN</u>	<u>N76°W</u>	<u>24.39</u>
	<u>STEEL FENCE POST</u>	<u>SOUTH</u>	<u>1.0</u>

Subsequent Corner Restoration

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
 Location filed \_\_\_\_\_  
 Monument \_\_\_\_\_

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_

Remonumentation certificate prepared \_\_\_\_\_

By \_\_\_\_\_

Filed at \_\_\_\_\_

Date \_\_\_\_\_