Index No. E 17

CASS COUNTY LAND CORNER RECORD

T. 138 R. 32 M. 5TH Coordinates: X _____ Y _____

NE 10 Corner common to sections 2, 3, 10, 11



EXISTING SURVEYS

Original Government Survey

Year surveyed 1870

Original monument Post

Bearing Trees

Species	TAm	TAm	TAm	TAm.
Diameter	9"	7"	9"	5"
Bearing	N46½E	N15½W	S48E	S6W
Distance	32 Lks.	33 Lks	12 Lks	6 Lks

Original Evidence Found

Year of search _____ By _____

Monument found _____

Original Bearing Trees Found

Species				
Diameter				
Bearing				
Distance				

Subsequent Corner Restoration

Year surveyed 1912 By JOHN CURO

Location filed COUNTY SURVEY RECORD BOOK "A" P408-414

Monument FND STUMPS OF OLD GOVT BITS: 9" TAm N46-30E 21.1', 7" TAM N15-30W 21.8', 9" TAm S48E 7.9', 5" TAm. S6W 4.0' SET 8X8X36" CONCRETE POST

COUNTY BOOK C P402 CONCRETE MONUMENT

Bearing Trees, Reference Objects

Species				
Diameter				
Bearing				
Distance				

Evidence of Subsequent Corner Restoration

Year of search OCT 1993 By K. DONAGHUE MN/DOT

FOUND 1912 CONC. MON. A 3/4" IRON PIN WAS PLACED OVER THE MON IN BITOMINOUS T.H #64

CERT. OF LOCATION DOC. # 433379

Bearing Trees, Reference Objects

TOP & W. END	CONC. CULV.	N30°W	61.60
TOP & E. END	CONC. CULV.	N16°E	60.80
N&D	3" ASPEN	N42°E	105.60
N&D	POWER POLE	S40°W	72.60

E-17

Subsequent Corner Restoration

Year surveyed JUNE 2000 By MN/DOT BAXTER

Location filed _____

Monument FOUND I.P. DOWN 3", LEANING. EXCAVATED 2± FOUND APPROX. 6"X8" STONE W/ POSSIBLE X. RTK & TIED OUT. FOUND NEXT TO ROCK N SIDE ¼ I.P POSSIBLY PLACED TO LOCATE.

SRP 8" POPPLE	UP 2± NW SIDE	NE	105.54
SRP T. PED.	UP 2± W. SIDE	SE	76.60
SRP P. POLE	UP 3± SE SIDE	SW	72.61

5/2001 MN/DOT Set PK nail for corner, 2000 witnesses ok.

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Remonumentation certificate prepared _____ By _____

Filed at _____ Date _____