Index No. E5

CASS COUNTY LAND CORNER RECORD

T. 138 R. 32 M. 5TH Coordinates: X _____ Y _____

NE 7 Corner common to sections 5, 6, 7, 8



EXISTING SURVEYS

Original Government Survey

Year surveyed 1870

Original monument POST

Bearing Trees

Species	SPRUCE	TAM	SPRUCE	TAM
Diameter	8"	12"	12"	9"
Bearing	SBE	S38½W	NBGE	NB5½W
Distance	300 LKS	54 LKS	365 LKS	390 LKS

Original Evidence Found

Year of search _____ By _____

Monument found _____

Original Bearing Trees Found

Species				
Diameter				
Bearing				
Distance				

Subsequent Corner Restoration

Year surveyed JUNE 1922 By J. CURO

Location filed CCSO

Monument FOUND "STAKE SET BY SOME SURVEYOR" NO SUPPORTING ACCESSORIES WERE RECOVERED.

Bearing Trees, Reference Objects

Species				
Diameter				
Bearing				
Distance				

Evidence of Subsequent Corner Restoration

Year of search MAY 1997 By K. DONAGHUE MN/DOT

FOUND WOOD POST 3' BELOW ROAD SURFACE. SET CAST IRON MON. ABOVE POST IN TWP RD. CERT. OF LOCATION Doc. # 433376

Bearing Trees, Reference Objects

N&D	POWER POLE	N48°E	61.97
N&D	5" ASPEN	S40°E	138.52
N&D	4" ASPEN	S44°W	133.70
N&D	4" ASPEN	N77°W	205.04

Subsequent Corner Restoration

Year surveyed _____ By _____

Location filed _____

Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Remonumentation certificate prepared _____ By _____

Filed at _____ Date _____