


Index No. V 21

CASS COUNTY LAND CORNER RECORD

T. 138 R. 32 M. 5TH Coordinates: X _____ Y _____
NE 35 Corner common to sections 25, 26, 35, 36



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1870
Original monument Post

Original Evidence Found

Year of search _____ By _____
Monument found _____

Species		Bearing		Trees	
<u>Bl. Pine</u>	<u>Bl. Pine</u>	<u>570E</u>	<u>N17 1/2 W</u>	<u>37 LKS</u>	<u>20 LKS</u>
Diameter <u>5"</u>	<u>4"</u>				
Bearing <u>570E</u>	<u>N17 1/2 W</u>				
Distance <u>37 LKS</u>	<u>20 LKS</u>				

Original Bearing Trees Found

Species _____	_____	_____	_____
Diameter _____	_____	_____	_____
Bearing _____	_____	_____	_____
Distance _____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1919 By E. B. Hoest
Location filed COUNTY BOOK 2, P. 159
Monument _____

Evidence of Subsequent Corner Restoration

Year of search 8/01 By Mn DOT
Set CIM, down 0.2', N. side of
20th St.

Species		Bearing		Trees, Reference Objects	
<u>J. Pine</u>	<u>J. Pine</u>	<u>N29-50E</u>	<u>N44-05W</u>	<u>541-37W</u>	<u>538-05E</u>
Diameter <u>8"</u>	<u>8"</u>				
Bearing <u>N29-50E</u>	<u>N44-05W</u>				
Distance <u>62.7'</u>	<u>61.8'</u>				

Species		Bearing		Trees, Reference Objects	
<u>J. Pine</u>	<u>P. Pole</u>	<u>NNE</u>	<u>SE</u>	<u>SW</u>	<u>NW</u>
Diameter <u>10"</u>	<u>8"</u>				
Bearing <u>NNE</u>	<u>SE</u>				
Distance <u>22.05'*</u>	<u>158.88'*</u>				

*distance to SRP

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Remonumentation certificate prepared _____
Filed at _____

By _____
Date _____