Index No. R 21

CASS COUNTY LAND CORNER RECORD

T. 139 R. 25 M. 5TH Coordinates: X _____ Y _____

NE 26 Corner common to sections 23, 24, 25, 26



O = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1863

Original monument POST

Original Evidence Found

Year of search _____ By _____

Monument found _____

Bearing Trees

Species	W. PINE	W. PINE	W. PINE	SPRUCE
Diameter	6"	8"	12"	8"
Bearing	N22E	N 62W	S55E	S25W
Distance	11 LKS.	29 LKS	29 LKS	33 LKS

Original Bearing Trees Found

Species				
Diameter				
Bearing				
Distance				

Subsequent Corner Restoration

Year surveyed 1910 By A.W. MOULSTER

Location filed _____

Monument FND ROLD GOVT B.T STUMPS: 6" W. PINE N22E 7.3', 8" SPRUCE S25W 21.8'
SET POST
also on microfilm - Roll 105 BK 48 P. 88

Bearing Trees, Reference Objects

Species	ELM	ASH		
Diameter	7"	14"		
Bearing	S4-12W	N75-19E		
Distance	49.10'	57'		

Evidence of Subsequent Corner Restoration

Year of search 1937 By CCC

Washburn Lake - BK # 2 P. 33
Set 4" Aspen post from which 12" Elm S31-30W 85' scribed W-B.T.

Bearing Trees, Reference Objects

R-21

Subsequent Corner Restoration

Year surveyed July 2004 By CCSO

Location filed CCSO #2003.009

Monument Set 7/8" OD IP, up 0.3', 70'± West of swale.

8" B. Oak	N8°W	23.95' *
9" Ash	S67°E	36.20' *
9" B. Oak	S21°W	27.00' *
6" Maple	S77°W	33.91' *

* distance to double head nail

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Remonumentation certificate prepared _____ By _____

Filed at _____ Date _____