


Index No. V 23

CASS COUNTY LAND CORNER RECORD

T. 139 R. 25 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
N 1/4 36 Corner common to sections 25, 36



EXISTING SURVEYS

Original Government Survey

Year surveyed 1863  
Original monument POST

Original Evidence Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

Bearing Trees	
Species	<u>SPRUCE ASPEN</u>
Diameter	<u>3" 12"</u>
Bearing	<u>N 5 E S R 5 E</u>
Distance	<u>7 LKS 25 LKS</u>

Original Bearing Trees Found	
Species	_____
Diameter	_____
Bearing	_____
Distance	_____

O = Corner

Subsequent Corner Restoration

Year surveyed 1937 By CCC  
Location filed Wushwin Lake - BK#1 P59  
Monument Set APP. cor 3" Birch post 2640 from E. 1937 BK#8. End old post point & stump of SE BIT. and root of NE BIT. Set 1 1/2 x 54" lip, 2 1/2" inground with 2 1/4" steel cap T139

Evidence of Subsequent Corner Restoration

Year of search 6/04 By CCSO  
Set 7/8" OD IP, up 0.4', 25't South of swamp. GPS

Bearing Trees, Reference Objects			
Species	<u>Balsam stub</u>	<u>Balsam</u>	<u>Balsam</u>
Diameter	<u>13 1/2"</u>	<u>10.7"</u>	<u>7 1/2"</u>
Bearing	<u>S 29 1/2 E</u>	<u>S 6 1/2 W</u>	<u>N 54 W</u>
Distance	<u>16.5'</u>	<u>34.9'</u>	<u>19.6'</u>

Bearing Trees, Reference Objects			
Species	<u>B. Oak</u>	<u>Aspen</u>	<u>Aspen</u>
Diameter	<u>4"</u>	<u>5"</u>	<u>5"</u>
Bearing	<u>N 50° W</u>	<u>N 68° E</u>	<u>S 11° E</u>
Distance	<u>31.02'*</u>	<u>14.08'*</u>	<u>19.41'*</u>

\* distance to double head nail

Subsequent Corner Restoration

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
Location filed \_\_\_\_\_  
Monument \_\_\_\_\_

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_

Remonumentation certificate prepared \_\_\_\_\_

By \_\_\_\_\_

Filed at \_\_\_\_\_

Date \_\_\_\_\_