


Index No. A 15

CASS COUNTY LAND CORNER RECORD

T. 139 R. 29 M. 5TH Coordinates: X _____ Y _____
N 1/4 3 Corner common to sections 3 AND 34 - 140-29 N.C. 4.48 CH. WEST



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1865
Original monument W.C. Post 4.48 CH. WEST

Original Evidence Found

Year of search _____ By _____
Monument found _____

Bearing Trees

Species BIRCH N. PINE
Diameter 10" 20"
Bearing S30W N75W
Distance 75 LKS. 40 LKS.

Original Bearing Trees Found

Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration

Year surveyed 1920 By J. Flynn
Location filed Book C, p. 359
Monument _____

Located corner from original BTS,
also on microfilm - roll 125 BK 170B P. 53
corner is 295.7' W. of true corner

Bearing Trees, Reference Objects

Species _____
Diameter _____
Bearing _____
Distance _____

Evidence of Subsequent Corner Restoration

Year of search 1969 By R.F. Schneider
Found 2" iron pipe in place and Gov't
Pine stump N75W 26.4'

Bearing Trees, Reference Objects

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Certificate - Landecker - 1984 DOC # 276687
Find 2" I.P. VP 1.5' SET 2x2x36" Steel post
W/cap 0.5 up.
Birch 6" N75W 31.75'
Roak 8" S85W 36.10'
Roak 8" S30W 24.60'

Remonumentation certificate prepared _____
Filed at _____

By _____
Date _____