


Index No. C 13

CASS COUNTY LAND CORNER RECORD

T. 139 R. 29 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
E 1/4 4 Corner common to sections 3, 4



EXISTING SURVEYS

Original Government Survey  
 Year surveyed 1865  
 Original monument Post

Original Evidence Found  
 Year of search \_\_\_\_\_ By \_\_\_\_\_  
 Monument found \_\_\_\_\_

Bearing Trees  
 Species Bl. Pine Bl. Pine  
 Diameter 10" 6"  
 Bearing N88W N46E  
 Distance 340 LKS 20 LKS

Original Bearing Trees Found  
 Species \_\_\_\_\_  
 Diameter \_\_\_\_\_  
 Bearing \_\_\_\_\_  
 Distance \_\_\_\_\_

Subsequent Corner Restoration  
 Year surveyed 1912 By JOHN Curo  
 Location filed COUNTY SURVEY RECORD BOOK "B" P. 200-211  
 Monument SET WOOD STAKE PROPORTIONALLY

Evidence of Subsequent Corner Restoration  
 Year of search 1945 By J. W. Curo  
Microfilm - roll 155 BK 271 P. 8-9  
Temp. 1/4 corner - 60 d spike  
also spike in heart of 14" J. Pine stump 543-44w  
38.35' (old scribed spot NE side - not orig)  
0.5' S of old E-W fence

Bearing Trees, Reference Objects  
 Species J. PINE POPULAR  
 Diameter 10" 6"  
 Bearing S 33-11 W N 48-18 W  
 Distance 33.80' 24.10'

Bearing Trees, Reference Objects  
BK 271 P. 24 - Temp cor. gets 1.09' N  
& 7.53' W to true corner.

Subsequent Corner Restoration  
 Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
 Location filed \_\_\_\_\_  
 Monument \_\_\_\_\_

Evidence of Subsequent Corner Restoration Found  
 Year of search \_\_\_\_\_ By \_\_\_\_\_  
Certificate - Landecker - 1984 Doc # 276697  
Find 2" i.p. down 0.2' set Co. cast iron  
down 0.5'  
J. Pine 7" North 22.22'  
J. Pine 10" S15E 31.65'  
J. Pine 9" S60W 93.15'  
N. Pine 6" N20W 50.12'

Remonumentation certificate prepared \_\_\_\_\_ By \_\_\_\_\_  
 Filed at \_\_\_\_\_ Date \_\_\_\_\_