


Index No. E7

CASS COUNTY LAND CORNER RECORD

T. 139 R. 30 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
N1/4 8 Corner common to sections 5, 8



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1865  
Original monument Post

Original Evidence Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

Bearing Trees  
Species BL. PINE BL. PINE  
Diameter 3" 12"  
Bearing N68W S76E  
Distance 46 LKS 59 LKS.

Original Bearing Trees Found

Species \_\_\_\_\_  
Diameter \_\_\_\_\_  
Bearing \_\_\_\_\_  
Distance \_\_\_\_\_

Subsequent Corner Restoration

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
Location filed \_\_\_\_\_  
Monument \_\_\_\_\_

Evidence of Subsequent Corner Restoration

Year of search \_\_\_\_\_ By \_\_\_\_\_

Bearing Trees, Reference Objects

Species \_\_\_\_\_  
Diameter \_\_\_\_\_  
Bearing \_\_\_\_\_  
Distance \_\_\_\_\_

Bearing Trees, Reference Objects

\_\_\_\_\_

Subsequent Corner Restoration

Year surveyed 1924 By Minn. Hwy Dept  
Location filed R/W map in Recorder's office  
Monument 1 1/2" iron in G Lot three to Pine Ave

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_

Certificate - Jim Nielsen - Minn DOT - Brainerd  
1983 Found railroad spike down 0.3'. Set  
Minn DOT cast iron monument. TIES:  
6" Jack Pine S80W 73.39'; 6" Jack Pine  
N45E 65.63'; 8" Red Oak S75E 108.79'  
Doc. #267944.

Remonumentation certificate prepared \_\_\_\_\_

By \_\_\_\_\_

Filed at \_\_\_\_\_

Date \_\_\_\_\_