


T. 139 R. 30 M. 5TH Coordinates: X _____ Y _____
N 1/4 29 Corner common to sections 20, 29



O = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1865
Original monument Post

Original Evidence Found

Year of search _____ By _____
Monument found _____

Bearing Trees

Species N. PINE N. PINE
Diameter 20" 20"
Bearing N65E SOUTH
Distance 55 LKS 180 LKS

Original Bearing Trees Found

Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration

Year surveyed 1911 By HARRY S. TODD
Location filed COUNTY SURVEY RECORD BOOK "A" P 373-377
Monument SET CORNER PROPORTIONALLY SET 2x4B"
CAPPED GALV. I.P. IN CONCRETE

Evidence of Subsequent Corner Restoration

Year of search 1924 By Minn Hwy Dept.
R/W map in Recorder's office - Lathrop to Pine River
stake at corner 17.0' W. of G

Bearing Trees, Reference Objects

Species _____
Diameter _____
Bearing _____
Distance _____

Bearing Trees, Reference Objects

R-7

Subsequent Corner Restoration

Year surveyed 7/01 By CCSO
Location filed file # 2001.035
Monument Found PK on paved shoulder,
14.5' W. of G Hwy #371, on G ext.
Hwy #87. 1983 R. Oak is good, add following
10" W. Oak N 28° W, 67.18' *
12" R. Oak S 78° W, 42.79' *
* distance to double head nail

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
Certificate - Jim Nelsen - Minn DOT - 1983
Found 3/4" iron pin down 6" on west shoulder
over 2" capped pipe.
Set MN/DOT cast iron monument down 0.5'
Ties: Tele. Red N50W 44.37'; 10" Red Oak N70W
39.71'; 8" Poplar S 85 W 37.05'; 15" Ash
560 W 52.47'.
Doc # 2107956.