


T. 140 R. 25 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
N14 11 Corner common to sections 2, 11



○ = Corner

EXISTING SURVEYS

**Original Government Survey**

Year surveyed 1867  
Original monument Post

Species	Bearing	Trees
<u>MAPLE</u>	<u>ASPEN</u>	
<u>5"</u>	<u>5"</u>	
<u>N32E</u>	<u>S36W</u>	
<u>5 LKS</u>	<u>4 LKS.</u>	

**Original Evidence Found**

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

**Original Bearing Trees Found**

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

**Subsequent Corner Restoration**

Year surveyed 1912 By HARRY S. TODD.  
Location filed COUNTY SURVEY RECORD BOOK A" P 552-555  
Monument FIND OLD GROUT BITS: 5" MAPLE N32E 5 LKS.  
STUMP 5" ASPEN S36W 4 LKS.

**Evidence of Subsequent Corner Restoration**

Year of search 1937 By CCC  
Washburn Lake - BK # 4 P. 21  
Old orig 1/4 cor. 4" sq Post 2690 from east

**Bearing Trees, Reference Objects**

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

**Bearing Trees, Reference Objects**

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

E-19

**Subsequent Corner Restoration**

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
Location filed \_\_\_\_\_  
Monument \_\_\_\_\_

**Evidence of Subsequent Corner Restoration Found**

Year of search \_\_\_\_\_ By \_\_\_\_\_

Cert. of Sale - Gary Stevenson 1984  
Doc. # 273704  
Set County cast iron monument. TIES:  
6" Maple N20 W 9.21'; 20" Maple N15 E  
71.50'; 10" Basswood S 80 W 64.95'.

1905, Twp. Road Order, C. Taylor,  
Surveyors Report indicates corner  
post.