


T. 140 R. 25 M. 5TH Coordinates: X _____ Y _____
E 1/4 7 Corner common to sections 7, 8



EXISTING SURVEYS

Original Government Survey

Year surveyed 1867

Original monument Post

| Species | Bearing | Tree |
|------------------------|--------------|------|
| <u>W. Pine</u> | <u>Birch</u> | |
| Diameter <u>5"</u> | <u>8"</u> | |
| Bearing <u>N31E</u> | <u>S51W</u> | |
| Distance <u>11 lks</u> | <u>9 lks</u> | |

Original Evidence Found

Year of search _____ By _____

Monument found _____

Original Bearing Trees Found

| Species | Bearing | Tree |
|----------------|---------|-------|
| _____ | _____ | _____ |
| Diameter _____ | _____ | _____ |
| Bearing _____ | _____ | _____ |
| Distance _____ | _____ | _____ |

O = Corner

Subsequent Corner Restoration

Year surveyed 1916 By ALOIS NOWAK

Location filed COUNTY SURVEY RECORD BOOK "B" P. 328-333

Monument FIND 2 1/2 X 2 1/2 PINE POST SET BY GUY TODD, STUMP OF OLD GUY BIT: 5" W. PINE N31E 11 LKS. ALSO TODD'S BITS: DOWN BIT AM, N45E 33.66'; STUMP 9" W. PINE S50W 44.88'

Bearing Trees, Reference Objects

| Species | Bearing | Tree |
|--|---------|------------|
| <u>also on microfilm - roll 105 BK 55 P 54</u> | | |
| Diameter _____ | | <u>55'</u> |
| Bearing _____ | | |
| Distance _____ | | |

Evidence of Subsequent Corner Restoration

Year of search 1914 By GUY TODD

Location filed COUNTY BOOK "B" P. 407-412 FIND OLD GUY BIT: 10" W. PINE N31E 11 LKS, SET 4X4X48 W. PINE STAKE

1937- CCC - Washburn Lake BK# 1 P. 40 SET APP Post 80.00 CH east of W/4 4" Aspen post

Bearing Trees, Reference Objects

| Species | Bearing | Tree |
|------------------|---------|------|
| <u>10"</u> | | |
| <u>W. PINE</u> | | |
| <u>N31-10W</u> | | |
| <u>22.30'</u> | | |
| <u>1914 BIT.</u> | | |

Subsequent Corner Restoration

Year surveyed 1956 By CCC

Location filed Washburn Lake BK# 3 P. 70

Monument Set 3" W. oak stake N. EDGE of Road

1956- DNR - Minn Forest Service Map in file
Corner on map

Evidence of Subsequent Corner Restoration Found

Year of search 1998 By CCSO

Found 1" IP PLS 9672 in E Co. Rd. #161

| |
|---|
| <u>6" Oak, N3°W, 33.08 16d spk</u> |
| <u>10" Oak, N75°E 52.93 16d spk</u> |
| <u>Balsam Snag S64°W, 48.51 16d spk</u> |
| <u>7" W. Oak, S60°E, 65.55 *</u> |
| <u>4" W. Oak, S47°W, 61.53 *</u> |
| <u>7" N. Pine, N45°W, 50.28 *</u> |

* distance to double head nail

1999 - Landecker - find iron monument in place. Cot 5 #497

1910, Twp Road Order, M. Watson, Surveyors Report indicates road on E-W 1/4 line.