


Index No. R13

CASS COUNTY LAND CORNER RECORD

T. 140 R. 25 M. 5TH Coordinates: X _____ Y _____
NE 28 Corner common to sections 21, 22, 27, 28



EXISTING SURVEYS

Original Government Survey
 Year surveyed 1867
 Original monument POST

| Species | Bearing | Trees |
|----------------|------------------|---------------|
| <u>W. PINE</u> | <u>FIR</u> | <u>FIR</u> |
| <u>6"</u> | <u>5"</u> | <u>4"</u> |
| <u>N5W</u> | <u>N32 3/4 E</u> | <u>S34E</u> |
| <u>43 LKS.</u> | <u>44 LKS</u> | <u>65 LKS</u> |

Original Evidence Found
 Year of search _____ By _____
 Monument found _____

Original Bearing Trees Found
 Species _____
 Diameter _____
 Bearing _____
 Distance _____

Subsequent Corner Restoration
 Year surveyed 1916 By E.B. HORST
 Location filed COUNTY BOOK 2 P. 538
 Monument END GOUT BITS: FIR N32-15E 44 LKS, AND
W. PINE SWAMP N5W 43 LKS SET CORNER.
4/500M MICROFILM - roll 105 BK 68 P. 20

Evidence of Subsequent Corner Restoration
 Year of search 1937 By CCC
Washburn Lake - BK # 3 P. 17
at 5200' from west - set approx corner.

Bearing Trees, Reference Objects

| Species | W. PINE | W. PINE | TAM | TAM |
|----------|--------------|---------------|--------------|--------------|
| Diameter | <u>5"</u> | <u>8"</u> | <u>3"</u> | <u>4"</u> |
| Bearing | <u>N29E</u> | <u>N70W</u> | <u>S40E</u> | <u>S75W</u> |
| Distance | <u>59.4'</u> | <u>83 LKS</u> | <u>30.8'</u> | <u>85.5'</u> |

Bearing Trees, Reference Objects

| Species | W. PINE | W. PINE | TAM | TAM |
|----------|---------|---------|-------|-------|
| Diameter | _____ | _____ | _____ | _____ |
| Bearing | _____ | _____ | _____ | _____ |
| Distance | _____ | _____ | _____ | _____ |

R-13

Subsequent Corner Restoration
 Year surveyed 1921 By M. Watson
 Location filed Twp. Road Orders
 Monument Surveyors Report indicates
road at corner.

Evidence of Subsequent Corner Restoration Found
 Year of search _____ By _____

Remonumentation certificate prepared _____ By _____
 Filed at _____ Date _____