


T. 140 R. 26 M. 5TH Coordinates: X _____ Y _____
N¹⁴ 8 Corner common to sections 5, 8



EXISTING SURVEYS

Original Government Survey

Year surveyed 1871
Original monument Post

Original Evidence Found

Year of search _____ By _____
Monument found _____

Bearing Trees
Species ASH Willow _____
Diameter 4" 5" _____
Bearing S17E N7W _____
Distance 13 LKS 14 LKS _____

Original Bearing Trees Found
Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration

Year of search 1938 By CCC
Found 3" Aspen stake 3' high scribed
"14-55" on north side and "1458" on
south side. Notes show corner in willow
swamp and an old east-west fence line,
2564.4 feet west to NW corner sec. 8

Bearing Trees, Reference Objects

Species _____
Diameter _____
Bearing _____
Distance _____

Bearing Trees, Reference Objects

E-7

Subsequent Corner Restoration

Year surveyed 1980 By G.H. Stevenson
Location filed _____
Monument Found iron set by T. Kerick
by using CCC distance from NW
corner of Sec. 8 and evidence of old
E-W fence line.

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
Certificate - Gary Stevenson - 1987
Doc # 295282

1983 - Gary Stevenson, check 10' set previously
replace with County cast iron

15" Twin Ash N36°E 52.30'
12" Burr Oak S61°E 87.70'
15" Ash S9°W 39.22'
17" Norway Pine S27°W 93.63'
Corner Certificate

Remonumentation certificate prepared _____ By _____
Filed at _____ Date _____