Index No. G 25

CASS COUNTY LAND CORNER RECORD

T. 140 R. 26 M. 5TH Coordinates: X _____ Y _____

E 1/4 1/2 Corner common to sections 12 AND 7-140-25



EXISTING SURVEYS

Original Government Survey

Year surveyed 1864

Original monument POST

Bearing Trees

Species	FIR	CEDAR		
Diameter	7"	8"		
Bearing	N24E	N53W		
Distance	16 lks	28 lks.		

Original Evidence Found

Year of search _____ By _____

Monument found _____

Original Bearing Trees Found

Species				
Diameter				
Bearing				
Distance				

Subsequent Corner Restoration

Year surveyed 1916 By ALOIS NOWAK

Location filed COUNTY SURVEY RECORD BOOK "B" P328-333

Monument FND OLD GOVT B.T STUMP: 8" CEDAR N53W 28 LKS, SET 3x3 BRASS POST

also on microfilm - roll 105 BK55 P.61, 76

Bearing Trees, Reference Objects

Species	W. PINE STUMP	W. PINE STUMP		
Diameter	18"	20"		
Bearing	N48W	NORTH		
Distance	18.70'	23'		

Evidence of Subsequent Corner Restoration

Year of search 1937 By CCC

Washburn Lake BK#1 P.39

Fnd 2" I.P. 80.26 CH. East of W 1/4

BK# 3 P.70 - I.P. in Twp road - 1956

1937- BK#4 P.30 - Start South from 2" I.P. 1020' to Lake

Bearing Trees, Reference Objects

G-25

Subsequent Corner Restoration

Year surveyed 1998 By CCSO

Location filed CCSO

Monument Found 1/2" IP (Cap gone) down 0.2', 2' S. of ℄,

(Old) 7" Tri Ash, dbl hd nail, S 50°E, 33.05'

(Old) 8" Twin Maple, dbl hd nail, S 36°W, 32.25'

12" Balsam, dbl hd nail, S 75°W, 69.89'

6" Ash, " " " N 38°E, 80.75"

Sept. 1910: M. Watson

Twp'd order shows survey

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Remonumentation certificate prepared _____ By _____

Filed at _____ Date _____