


Index No. V 25

CASS COUNTY LAND CORNER RECORD

T. 140 R. 28 M. 5th Coordinates: X _____ Y _____
NE 36 Corner common to sections 29, 36 AND 30, 31-140-27



○ = Corner

EXISTING SURVEYS

Original Government Survey
Year surveyed 1863
Original monument Post

Original Evidence Found
Year of search _____ By _____
Monument found _____

Species	Bearing Trees			
	J. Pine	J. Pine	TAM.	J. Pine
Diameter	6"	6"	5"	6"
Bearing	N17E	S27E	S79W	N23W
Distance	36 LKS	23 LKS	29 LKS	8 LKS
	23	29	8	22

Original Bearing Trees Found	
Species	_____
Diameter	_____
Bearing	_____
Distance	_____

Subsequent Corner Restoration
Year surveyed 1939 By JOHN CURD
Location filed COUNTY BOOK "D" P. 235
Monument SET 2x4" I.P. TRIMWOOD GWT BITS!

Evidence of Subsequent Corner Restoration
Year of search 1938 By CC
Washburn Lake - BK# 9 P. 6
Start east from iron pipe and 3" stake
1939 - BK# 13 P. 2 - at 5400' from South find
I.P. 1 1/2" and 3" sq stake also both BITS below.
BK# 20 - 375' N & 880' west of control posts on
old grade

Species	Bearing Trees, Reference Objects			
	REMAINS OF J. PINE STUMP	J. PINE STUMP	J. PINE	J. PINE
Diameter	U.S. BIT	6"	5"	REMAINS
Bearing	N17E	N23W	S79W	S27E
Distance	15.10'	14.52'	5.20'	19.14'

Bearing Trees, Reference Objects	
Tam	Tam
10"	10"
S33 1/2 E	N70E
25'	17.5'

Subsequent Corner Restoration
Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found
Year of search _____ By _____

Remonumentation certificate prepared _____ By _____
Filed at _____ Date _____