


T. 140 R. 29 M. 5TH Coordinates: X _____ Y _____
NE 22 Corner common to sections 14, 15, 22, 23



EXISTING SURVEYS

Original Government Survey
 Year surveyed 1870
 Original monument POST

Species	Bearing	Trees	Distance
<u>Basswood</u>	<u>Maple</u>	<u>Maple</u>	<u>Maple</u>
<u>5"</u>	<u>5"</u>	<u>5"</u>	<u>12"</u>
<u>N 50 E</u>	<u>N 22 W</u>	<u>S 64 W</u>	<u>S 35 E</u>
<u>10 lks</u>	<u>49 lks</u>	<u>51 lks</u>	<u>35 lks</u>

Original Evidence Found
 Year of search _____ By _____
 Monument found _____

Original Bearing Trees Found

Species	Diameter	Bearing	Distance

Subsequent Corner Restoration
 Year surveyed 1919 By E. B. HORST
 Location filed COUNTY RESURVEY 'E-24'
 Monument 2" x 30" IRON MONUMENT
1926 - JOHN GREENE COUNTY RESURVEY 'E-25' J. M.
1919, E. B. HORST, BOOK 'D' P. 32 SET STAKE FROM
N. W. B. T. (STANDING) AND STUMPS OF OTHER B. T.S.

Evidence of Subsequent Corner Restoration
 Year of search 1990 By WALT CURT
END 2 1/2" X 30" IRON PIPE LYING IN DITCH
RESET 2" X 2" X 18" TELESPAR MON W/AL. CAP
FROM BT'S FROM G. STEVENSON SET 1" X
8" PIPE ON TOP

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
<u>MAPLE</u>	<u>8"</u>	<u>N 35-15 E</u>	<u>38.6'</u>
<u>MAPLE</u>	<u>9"</u>	<u>N 31 W</u>	<u>43.0'</u>
<u>BALSAM</u>	<u>6"</u>	<u>S 48-10 W</u>	<u>36.5'</u>
<u>BASSWOOD</u>	<u>10"</u>	<u>S 75 E</u>	<u>29.7'</u>

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance

Subsequent Corner Restoration
 Year surveyed _____ By _____
 Location filed _____
 Monument _____

Evidence of Subsequent Corner Restoration Found
 Year of search _____ By _____
PLAT - END O' THE TRAIL SECOND ADDITION
O. G. NOWAK 1972
PLAT - END O' THE TRAIL THIRD ADDITION
O. G. NOWAK 1972
DNR FILE - Certificate started
1992 Cert. Filed by John Walker / DNR
Doc. # 343675
Found 3" square aluminum capped County
monument (down 0.9') and 1.5' north
of E E-W gravel road. Ties: 18" White
Pine N 10 E 27.45'; 14" Red Oak S 70 E 47.89';
24" White Pine S 4 E 27.22'; 12" Maple
S 30 W 31.31'.