


T. 146 R. 30 M. 5TH Coordinates: X _____ Y _____
NE 10 Corner common to sections 2, 3, 10, 11



○ = Corner

EXISTING SURVEYS

Original Government Survey
 Year surveyed 1865
 Original monument POST

Bearing Trees		Bearing Trees	
Species	Diameter	Species	Diameter
<u>W. PINE</u>	<u>30"</u>	<u>N. PINE</u>	<u>24"</u>
<u>W. PINE</u>	<u>30"</u>	<u>N. PINE</u>	<u>18"</u>
<u>N34 1/2 E</u>	<u>52 LKS</u>	<u>N49 1/2 W</u>	<u>95 LKS</u>
<u>52 LKS</u>		<u>96 LKS</u>	

Original Evidence Found
 Year of search _____ By _____
 Monument found _____

Original Bearing Trees Found

Species	Diameter	Bearing	Distance

Subsequent Corner Restoration
 Year surveyed 1965 By DNR
 Location filed Map notes in file
 Monument End 1" I.P. down 0.1' at P. 1. roads N & W and fence S.

Evidence of Subsequent Corner Restoration
 Year of search 1975 By R.F. SCHNEIDER
FOUND 1 1/2" I.P. REPLACED WITH CAST IRON ON E OF ROAD WEST & FENCE SOUTH

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
<u>J. PINE</u>	<u>12"</u>	<u>SW</u>	<u>38.40'</u>
<u>W. OAK</u>	<u>10"</u>	<u>SSE</u>	<u>34.18'</u>
<u>W. OAK</u>	<u>5"</u>	<u>NW</u>	<u>25.14'</u>
			<u>Nail in B.C.</u>

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
<u>J. PINE</u>	<u>6"</u>	<u>N40W</u>	<u>70.70</u>
<u>W. OAK</u>	<u>4"</u>	<u>N45E</u>	<u>51.98</u>
<u>W. OAK</u>	<u>8"</u>	<u>S29E</u>	<u>30.62</u>
<u>J. PINE</u>	<u>6"</u>	<u>S70W</u>	<u>31.47</u>
			<u>DOUBLE BLAZED, NAILS IN SIDE</u>

Subsequent Corner Restoration
 Year surveyed _____ By _____
 Location filed _____
 Monument _____

Evidence of Subsequent Corner Restoration Found
 Year of search _____ By _____
CERTIFICATE - R.F. SCHNEIDER - 1976
Doc. # 224014
Found 1 1/2" pipe. Set County cast iron monument 4" dia. top x 20" long, buried 3" below grade. Ties: 6" Jack Pine N40W 70.70'; 4" W. Oak N45E 51.98'; 8" W. Oak S29E 30.62'; 6" J. PINE S70W 31.47'.
Feb. 2005 T Freeman #21367
Cert. of Survey shows monument found