


Index No. N 23

CASS COUNTY LAND CORNER RECORD

T. 140 R. 30 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
N 1/4 24 Corner common to sections 13, 24



○ = Corner

EXISTING SURVEYS

Original Government Survey  
 Year surveyed 1865  
 Original monument POST

Original Evidence Found  
 Year of search \_\_\_\_\_ By \_\_\_\_\_  
 Monument found \_\_\_\_\_

Bearing Trees  
 Species IRONWOOD SUGAR  
 Diameter 5" 6"  
 Bearing S 71 E N 55 E  
 Distance 6 LKS 18 LKS

Original Bearing Trees Found  
 Species \_\_\_\_\_  
 Diameter \_\_\_\_\_  
 Bearing \_\_\_\_\_  
 Distance \_\_\_\_\_

Subsequent Corner Restoration  
 Year surveyed 1907 By JOHN CURD  
 Location filed COUNTY BOOK B' P. 433-441  
 Monument FIND POINT OF OLD STAKE AND OLD GOLT BITS:  
PART 6" MAPLE N 55 E 18 LKS, ROOTS 5" IRONWOOD  
S 71 E 6 LKS SET NEW STAKE

Evidence of Subsequent Corner Restoration  
 Year of search 1965 By R.F. SCHNEIDER  
COUNTY BOOK 'D' P. 443 FIND I.P. (NEW TIES)

Bearing Trees, Reference Objects  
 Species \_\_\_\_\_  
 Diameter \_\_\_\_\_  
 Bearing \_\_\_\_\_  
 Distance \_\_\_\_\_

Bearing Trees, Reference Objects  

<u>W. OAK</u>	<u>W. OAK</u>	<u>W. OAK</u>
<u>5"</u>	<u>6"</u>	<u>5"</u>
<u>N 50 W</u>	<u>N 13 E</u>	<u>N 44 1/2 E</u>
<u>3.55'</u>	<u>30.8'</u>	<u>17.55'</u>

N-23

Subsequent Corner Restoration  
 Year surveyed 1965 By R.F. Schneider  
 Location filed DNR FILE - map in file  
 Monument Found iron marker in place

Evidence of Subsequent Corner Restoration Found  
 Year of search \_\_\_\_\_ By \_\_\_\_\_

Remonumentation certificate prepared \_\_\_\_\_ By \_\_\_\_\_  
 Filed at \_\_\_\_\_ Date \_\_\_\_\_