Index No. N 9

CASS COUNTY LAND CORNER RECORD

T. 140 R. 30 M. 5TH Coordinates: X _____ Y _____

NE 20 Corner common to sections 16,17,20,21 W.C. 30 CH. NORTH



EXISTING SURVEYS

Original Government Survey

Year surveyed 1865

Original monument POST W.C. 30 LKS NORTH

Bearing Trees

Species	N. PINE	N. PINE
Diameter	20"	20"
Bearing	N55W	N34E
Distance	103 LKS.	94 LKS

Original Evidence Found

Year of search _____ By _____

Monument found _____

Original Bearing Trees Found

Species				
Diameter				
Bearing				
Distance				

Subsequent Corner Restoration

Year surveyed 1907 By JOHN CURO

Location filed COUNTY BOOK "B" P. 433-441

Monument FND W.C. BITS: STUMP 20" N. PINE N34E 94 LKS, 20" N. PINE N55W 103 LKS. SET 4X4X60" PINE POST

1921-E.B. HOREST - COUNTY RESURVEY - "E-36" W.C. 19.8' NORTH

Bearing Trees, Reference Objects

Species				
Diameter				
Bearing				
Distance				

Evidence of Subsequent Corner Restoration

Year of search 1918 By E.B. HOREST

COUNTY BOOK "C" P. 104 FND W.C. B.TS AND POST SET 2X4X8" I.M. AT W.C AND 2X4X8" I.M. AT TRUE CORNER TO 16-17-20-21

1921, E.B. HOREST, BOOK "E" P440. FND CORNER & W.C. - ALSO ON MICROFILM - ROLL 105 BK 59, P. 42

Bearing Trees, Reference Objects

Subsequent Corner Restoration

Year surveyed 2000 JULY By CCSO

Location filed

Monument Fnd. in place; 2" ODIP, dwn. 0.5'. Located E Twp Rd. (40th Ave NW)

REF TIES:

11" R. Oak N 32°W 85.24'

9" Ash N 14°E 71.31'

* distance to dbl. hd. nail

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Remonumentation certificate prepared _____ By _____

Filed at _____ Date _____