


Index No. V3

CASS COUNTY LAND CORNER RECORD

T. 146 R. 30 M. 5TH Coordinates: X _____ Y _____
N 1/4 31 Corner common to sections 30, 31



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1865
Original monument Post

Original Evidence Found

Year of search _____ By _____
Monument found _____

Bearing Trees

Species BL. PINE BL. PINE _____
Diameter 10" 12" _____
Bearing N6W S30E _____
Distance 4 LKS 11 LKS _____

Original Bearing Trees Found

Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration

Year of search _____ By _____

Bearing Trees, Reference Objects

Species _____
Diameter _____
Bearing _____
Distance _____

Bearing Trees, Reference Objects

V-3

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Certificate - Jim Nielsen - Minn DOT 1983
Doc. # 267933
Set MN/DOT cast iron monument. TIES:
witness post 1.75' North; 10" Jack Pine
5.74 W 59.74'; 60d spike 554°18'E 10.10';
4" White Oak 56 W 47.82'; 10" Jack Pine
5.30 E 93.42'.

Remonumentation certificate prepared _____

By _____

Filed at _____

Date _____