


T. 141 R. 25 M. 5TH Coordinates: X _____ Y _____

NE 16 Corner common to sections 9, 10, 15, 16



EXISTING SURVEYS

Original Government Survey
 Year surveyed 1871
 Original monument POST

Original Evidence Found
 Year of search _____ By _____
 Monument found _____

Species	Bearing	Trees	
<u>FIR</u>	<u>ASPEN</u>	<u>BIRCH</u>	<u>W. PINE</u>
Diameter <u>10"</u>	<u>10"</u>	<u>8"</u>	<u>10"</u>
Bearing <u>S15E</u>	<u>S63W</u>	<u>N46E</u>	<u>N77W</u>
Distance <u>28LKS</u>	<u>22LKS</u>	<u>17LKS</u>	<u>14LKS</u>

Original Bearing Trees Found

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Subsequent Corner Restoration
 Year surveyed 1913 By J.H. FLYNN
 Location filed COUNTY BOOK "C" P. 37
 Monument END OLD GOVT B.T.S. W. PINE STUB N77W 14 LKS,
ROTTEN FIR STUMP 10" S15E 28LKS

Evidence of Subsequent Corner Restoration
 Year of search 1985 By USFS
Corner Certificate - Doc # 285567
set 2 1/2 x 2 1/4" l.p. w/ stamped brass cap
in intersection of roads - distances fit well
w: s.

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
<u>W. PINE STUMP DRY CEDAR</u>	<u>15"</u>	<u>10'</u>	
		<u>N72E</u>	<u>39.5'</u>
			<u>56.5'</u>

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
<u>W. oak</u>	<u>8.5"</u>	<u>N45E</u>	<u>125.70'</u>
<u>W. Birch</u>	<u>9.5"</u>	<u>S60E</u>	<u>72.13'</u>
<u>W. Birch</u>	<u>6.3"</u>	<u>S69W</u>	<u>61.89'</u>
<u>W. oak</u>	<u>6.7"</u>	<u>N35W</u>	<u>87.83'</u>

Subsequent Corner Restoration
 Year surveyed _____ By _____
 Location filed _____
 Monument _____

Evidence of Subsequent Corner Restoration Found
 Year of search _____ By _____
Certificate - Ken Whitehorn - USFS - 1985