

Index No. _____

CASS COUNTY LAND CORNER RECORD

T. _____ R. _____ M. _____ Coordinates: X _____ Y _____

Corner common to sections _____



= Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed _____
Original monument _____

Original Evidence Found

Year of search _____ by _____
Monument found _____

Bearing Trees

Species _____
Diameter _____
Bearing _____
Distance _____

Original Bearing Trees Found

Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed:
Monument:

Evidence of Subsequent Corner Restoration

Year of search _____ By _____
Location filed:
Monument:

Bearing Trees, Reference Objects

Species _____
Diameter _____
Bearing _____
Distance _____

Bearing Trees, Reference Objects

Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed:
Monument:


Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
Location filed:
Monument:

Index No. A 17

CASS COUNTY LAND CORNER RECORD

T. 141 R. 26 M. 5TH Coordinates: X _____ Y _____
NE 3 Corner common to sections R. 3 AND 34, 35 - 142-26



EXISTING SURVEYS

Original Government Survey

Year surveyed 1971

Original monument POST

Species	Bearing	Trees	W. PINE
<u>SPRUCE</u>	<u>SPRUCE</u>	<u>SPRUCE</u>	<u>W. PINE</u>
Diameter <u>12"</u>	<u>10"</u>	<u>6"</u>	<u>24"</u>
Bearing <u>N22W</u>	<u>N6E</u>	<u>S44E</u>	<u>S18W</u>
Distance <u>10 LKS</u>	<u>17 LKS</u>	<u>15 LKS</u>	<u>37 LKS</u>

Original Evidence Found

Year of search _____ By _____

Monument found _____

Original Bearing Trees Found

Species	Bearing	Trees	Distance
_____	_____	_____	_____
Diameter _____	_____	_____	_____
Bearing _____	_____	_____	_____
Distance _____	_____	_____	_____

○ = Corner

Subsequent Corner Restoration

Year surveyed 1972 By JAMES ELYNN

Location filed COUNTY BOOK "D" P 51

Monument FIND OLD GOLT BIT: STUMP 6' HIGH 24" W. ANE S18W 37 LKS AND AN IRON PIPE

Bearing Trees, Reference Objects

Species	Bearing	Distance
_____	_____	_____
Diameter _____	_____	_____
Bearing _____	_____	_____
Distance _____	_____	_____

Evidence of Subsequent Corner Restoration

Year of search 1951 By HAROLD CURO

BOOK "D" P. 376 FIND IRON IN PLACE, BUT TWISTED OUT OF SHAPE SET 120 d SPIKE

Bearing Trees, Reference Objects

Species	Bearing	Distance
<u>SPRUCE</u>	<u>W. OAK</u>	<u>12" TELE POLE</u>
<u>10"</u>	<u>5"</u>	<u>516-530</u>
<u>N77-12E</u>	<u>N14-30W</u>	<u>82.35'</u>
<u>140.50'</u>	<u>79.25'</u>	<u>536-40E</u>
		<u>126.80'</u>

A-17

Subsequent Corner Restoration

Year surveyed _____ By _____

Location filed _____

Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

CERTIFICATE - BILL OKERMAN - 1964

Certificate - Walt Curo - 1986

Find 3/4" iron pin over concrete monument

7" W. OAK N 70° W 166.31'

8" N. Pine N 67° E 69.89'

8" Spruce S 70° E 83.87'

NE Cor. House S 45° W 170.16'

DWD # 291475

Aug. 2003 M. Stefan # 12261

Cert. of Sur. shows mon found

Jan 2005 T. Freeman # 21367

Cert of survey indicates monument found

June 2005 T. Freeman # 21367

Cert. of Survey shows monument found