


T. 141 R. 27 M. 5th Coordinates: X _____ Y _____
NE 15 Corner common to sections 10, 11, 14, 15



EXISTING SURVEYS

Original Government Survey

Year surveyed 1874
Original monument Post

Original Evidence Found

Year of search _____ by _____
Monument found _____

Bearing Trees

Species	<u>Norway Pine</u>	<u>Poplar</u>	<u>Poplar</u>
Diameter	<u>20"</u>	<u>7"</u>	<u>7"</u>
Bearing	<u>N 40° W</u>	<u>S 52° W</u>	<u>S 65° E</u>
Distance	<u>70 links</u>	<u>70 links</u>	<u>105 links</u>

Original Bearing Trees Found

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1941 By R.T. Defant, CCC
Location filed: USFS Field Book 2, page 48
Monument: Found Iron Pipe
5" below road, in good condition, lines up with W. side of open field, FSLP on following.

Evidence of Subsequent Corner Restoration

Year of search 11/1967 By J. Ekstrom, USFS
Location filed: USFS Field Book 2, page 48
Monument: Found iron pipe
as described in 1941 notes.

Bearing Trees, Reference Objects

Species	_____	_____	_____
Diameter	<u>8"</u>	_____	_____
Bearing	<u>N 40° E</u>	_____	_____
Distance	<u>28.4'</u>	_____	_____

Bearing Trees, Reference Objects

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 6/1968 By L. Elliott, USFS
Location filed: USFS Field Book 2, page 48 T141N R27W
Monument: Set 6" concrete cylinder W/brass cap S 10 | S 11
down 1' in road intersection and witnessed. S 15 | S 14
12" White Oak, N 44° E, 36.9' scribed 1968
10" Red Pine, N 28° W, 79.72' scribed RLS No. 6807
7" Red Pine, N 65° W, 100.63' scribed
6" White Oak, S 28° W, 45.96' scribed
4" Cedar Post, South, 8.85' 54-2 and 54-4 signs

Evidence of Subsequent Corner Restoration Found

Year of search 6/1997 By R. Main, USFS
Location filed: USFS Field Book 2, page 48 T141N R27W
Monument: Found USFS concrete monument S 10 | S 11
broken and flush, in Co. Rd. #129. Remove S 15 | S 14
and replace with 2"x 24" USFS iron pipe with 1997
brass cap, down 1'1" and witnesses. USFS
16" White Oak, N 44° E, 36.90'(1968) 60d spike
17" Red Pine, N 28° W, 79.72'(1968) 60d spike
16" Red Pine, N 65° W, 100.63'(1968) 60d spike
10" Quad White Oak, S 28° W, 45.96'(1968) 60d spike


10/1987, R.L. Kovanen, LS 16459
Certificate of Location, #302622
Found USFS brass cap in concrete, down 0.5', 5'+/-, E. of
centerline Co. Rd. #129 P.I. and 2" iron pipe, 1.25' SW of
concrete monument, witnesses as follows.
14" White Oak, N 44° E, 36.90'(1968) 20d spike
12" Red Pine, N 28° W, 79.72'(1968) 20d spike
9" Red Pine, N 65° W, 100.63'(1968) 20d spike
8" Twin White Oak, S 28° W, 45.96'(1968) 20d spike
4" Cedar Post, South, 8.85'(1968) 54-2 and 54-4 signs
Steel Sign Post, South, 23.93'

10/2005, CCHD/SO
#2001.016
Set a spike and washer from witnesses and located with GPS.
8/2018, CCHD/SO
#2017.018
Found 2" IP, 1.25' SW of corner set from witnesses, down 1.2'

Index No. J 17

CASS COUNTY LAND CORNER RECORD

T. 141 R. 27 M. 5TH Coordinates: X _____ Y _____
NE 15 Corner common to sections 10, 11, 14, 15



EXISTING SURVEYS

Original Government Survey
 Year surveyed 1874
 Original monument POST

Original Evidence Found
 Year of search _____ By _____
 Monument found _____

	Bearing	Trees
Species	<u>N. PINE</u>	<u>POPLAR</u>
Diameter	<u>20"</u>	<u>7"</u>
Bearing	<u>N40W</u>	<u>552W</u>
Distance	<u>70 LKS.</u>	<u>70 LKS</u>

Original Bearing Trees Found
 Species _____
 Diameter _____
 Bearing _____
 Distance _____

○ = Corner

Subsequent Corner Restoration
 Year surveyed _____ By _____
 Location filed _____
 Monument _____

Evidence of Subsequent Corner Restoration
 Year of search 1988 By Robert Kovanen
Corner Certificate - Doc # 302622
Find brass cap concrete monument

Bearing Trees, Reference Objects
 Species _____
 Diameter _____
 Bearing _____
 Distance _____

Bearing Trees	Reference Objects
<u>Red Pine</u>	<u>W. Oak</u>
<u>12"</u>	<u>8" Twin</u>
<u>N28W</u>	<u>528W</u>
<u>79.72'</u>	<u>45.96'</u>

Subsequent Corner Restoration
 Year surveyed _____ By _____
 Location filed _____
 Monument _____

Evidence of Subsequent Corner Restoration Found
 Year of search _____ By _____
CERTIFICATE - BILL OKERMAN - 1968
Certificate - Robert Kovanen - 1988
July 2003 R. Mustonen #11946
Cert. of Surv. shows Mon. found

Remonumentation certificate prepared 2/2/88
 Filed at Cass Co. Recorder's Office #302622

By Kovanen #16459
 Date 2/2/88