


T. 141 R. 27 M. 5TH Coordinates: X _____ Y _____
NE 13 Corner common to sections 12, 13 and 7, 16-141-26



EXISTING SURVEYS

Original Government Survey

Year surveyed 1871
Original monument POST

Original Evidence Found

Year of search _____ By _____
Monument found _____

	Bearing Trees		
Species	<u>ELM</u>	<u>BIRCH</u>	<u>FIR</u>
Diameter	<u>16"</u>	<u>14"</u>	<u>8"</u>
Bearing	<u>SSW</u>	<u>N70E</u>	<u>N10W</u>
Distance	<u>20 LKS</u>	<u>51 LKS</u>	<u>32 LKS</u>

Original Bearing Trees Found			
Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1968 By W.W. OKERMAN
Location filed _____
Monument PLACED A 6" X 6" CONCRETE
MON. WITH DR. / CAP

Evidence of Subsequent Corner Restoration

Year of search 1987 By TERRY FREEMAN
FIND 1968 OT'S
2-STEEL SIGN POSTS N45W 9.68 + N45E 9.80
2-ALUM SIGN POSTS S45W 8.55 + S45E 9.48
1968 TREES IN PLACE

Bearing Trees, Reference Objects

	<u>DAK</u>	<u>BURR OAK</u>	<u>R6D OAK</u>
Species			
Diameter	<u>4</u>	<u>10</u>	<u>13</u>
Bearing	<u>N10W</u>	<u>N45E</u>	<u>S44E</u>
Distance	<u>47.25</u>	<u>92.25</u>	<u>91.70</u>

Bearing Trees, Reference Objects

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 2/14/2000 By M. WADSWORTH LAND DEPT
Location filed _____
Monument RESOURCE GRADE GPS NAD 83
UTM METERS N = 184683.5
E = 546714.2

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
CERTIFICATE - BILL OKERMAN - 1968
CERTIFICATE WALT CURD 1990
Doc. No. 318884