


Index No. M 7

CASS COUNTY LAND CORNER RECORD

T. 141 R. 27 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
C.S. 1/16 Corner common to sections 17



○ = Corner

EXISTING SURVEYS

**Original Government Survey**  
 Year surveyed 1919  
 Original monument 1x36" I.P. W/BRASS CAP. 5/16/517 1919

**Bearing Trees**  
 Species W. PINE W. PINE  
 Diameter 10" 10"  
 Bearing S89-15E S1-45W  
 Distance 39 LKS 61 LKS

**Original Evidence Found**  
 Year of search \_\_\_\_\_ By \_\_\_\_\_  
 Monument found \_\_\_\_\_

**Original Bearing Trees Found**  
 Species \_\_\_\_\_  
 Diameter \_\_\_\_\_  
 Bearing \_\_\_\_\_  
 Distance \_\_\_\_\_

**Subsequent Corner Restoration**  
 Year surveyed 1982 By Gary Stevenson  
 Location filed Corner Certificate  
 Monument In 1980 USFS Found brass cap bent straightened and reset using stumps of BETA B.T.S 12" w. pine stump S89E 25.7'; 12" w. pine stump S2 W 40.2'

**Bearing Trees, Reference Objects**  
 Species W. OAK W. OAK W. OAK  
 Diameter 7" 6" 6"  
 Bearing N43E N65E N86W  
 Distance 50.9' 26.1' 29.1'

**Evidence of Subsequent Corner Restoration**  
 Year of search \_\_\_\_\_ By \_\_\_\_\_

**Bearing Trees, Reference Objects**  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

**Subsequent Corner Restoration**  
 Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
 Location filed \_\_\_\_\_  
 Monument \_\_\_\_\_

**Evidence of Subsequent Corner Restoration Found**  
 Year of search \_\_\_\_\_ By \_\_\_\_\_  
Certificate - Gary Stevenson - Filed by USFS 1984  
Doc. # 279270 dated 1982

Remonumentation certificate prepared \_\_\_\_\_ By \_\_\_\_\_  
Filed at \_\_\_\_\_ Date \_\_\_\_\_