


Index No. R17

CASS COUNTY LAND CORNER RECORD

T. 141 R. 27 M. 5TH Coordinates: X _____ Y _____
NE 27 Corner common to sections 22, 23, 26, 27



EXISTING SURVEYS

Original Government Survey

Year surveyed 1874
Original monument POST

Original Evidence Found

Year of search _____ By _____
Monument found _____

Bearing Trees

Species DEMO CEDAR DEMO CEDAR
Diameter 6" 5"
Bearing N40E S33W
Distance 65LKS 19LKS

Original Bearing Trees Found

Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration

Year surveyed 1920 By LINCOLN MCKEY
Location filed COUNTY BOOK "E" P. 379
Monument SET CORNER PROPORTIONALLY SET 2x10" I.M.

Evidence of Subsequent Corner Restoration

Year of search _____ By _____

Bearing Trees, Reference Objects

Species SPRUCE SPRUCE SPRUCE SPRUCE
Diameter 5" 5" 6" 5"
Bearing N49E S44 1/4 E S62 3/4 W N52W
Distance 48.5' 51.5' 30.3' 30.6'

Bearing Trees, Reference Objects

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
CERTIFICATE - BILL OKERMAN - 1968
Found snag for 8" Tamarack N15W 29.1'
Set 2"x5' galvanized steel monument
filled with concrete and capped with 3"
stamped brass cap. Ties: 8" Tamarack
S82W 52.7'; 5" Tamarack N35W 14.4'
8" Cedar N57E 34.4'; 6" Cedar S4E
41.2'
1993 12-11: Found 2"x5' galv. steel monument.
Left as found. 3-4-94 placed 2"x24" galv.
steel monument w/brass cap on top of 8"
steel sign post. Ties: 7" Black Spruce N63E
28.94'; 6" Black Spruce N22W 27.81'; 8" Black
Spruce S40W 14.94'; 5" Black Spruce S47E
13.78'
5-4-94 Cert. Filed By Terry Freeman, R65 21367,
Doc. #357307.

Remonumentation certificate prepared _____
Filed at _____

By _____
Date _____