


T. 141 R. 27 M. 5TH Coordinates: X _____ Y _____
E14 34 Corner common to sections 34, 35



O = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1874
Original monument POST

Original Evidence Found

Year of search _____ By _____
Monument found _____

Bearing Trees

Species	<u>N. PINE</u>	<u>N. PINE</u>	_____	_____
Diameter	<u>18"</u>	<u>14"</u>	_____	_____
Bearing	<u>N67W</u>	<u>S25W</u>	_____	_____
Distance	<u>30LKS</u>	<u>57LKS</u>	_____	_____

Original Bearing Trees Found

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1974-1978 By MILO STEPAN - USFS
Location filed PLAT OF SURVEY "E-72"
Monument 2"x5" GALV I.P. w/3" BRASS CAP (PROPORTIONED)

Evidence of Subsequent Corner Restoration

Year of search 1976 By DNR-Engineering
Preliminary Certificate in file

IN 1976 - USFS set 2x60" I.P. w/brass cap

Bearing Trees, Reference Objects

Species	<u>W. OAK</u>	<u>W. OAK</u>	<u>W. OAK</u>	<u>TWIN ELM</u>
Diameter	<u>16"</u>	<u>8"</u>	<u>7"</u>	<u>7" & 9"</u>
Bearing	<u>S15W</u>	<u>S39W</u>	<u>S65E</u>	<u>S65E</u>
Distance	<u>46.4'</u>	<u>99.8'</u>	<u>24.0'</u>	<u>1.3'</u>

Bearing Trees, Reference Objects

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search 1993 12-14 By Terry Freeman
Found 5"x5" galvanized iron pipe w/3" brass cap. Left as found. 5-4-94 Cert. Filed by Terry Freeman, RLS 21367, Doc. #357318. Ties: 12" White Oak S39W 99.80' (1976 USFS BT); 20" White Oak S15W 46.40' (1976 USFS BT); SW Corner Cabin S39E 63.6'; NE corner Cabin S74E 108.6'; 12" White Oak S65E 24.00' (1976 USFS BT)

Remonumentation certificate prepared _____

By _____

Filed at _____

Date _____