

Index No. _____

CASS COUNTY LAND CORNER RECORD

T. _____ R. _____ M. _____ Coordinates: X _____ Y _____

Corner common to sections _____

= Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed _____
Original monument _____

Original Evidence Found

Year of search _____ by _____
Monument found _____

Bearing Trees

Species _____
Diameter _____
Bearing _____
Distance _____

Original Bearing Trees Found

Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed:
Monument:

Evidence of Subsequent Corner Restoration

Year of search _____ By _____
Location filed:
Monument:
S21 | S22
S28 | S27
1918

Bearing Trees, Reference Objects

Species _____
Diameter _____
Bearing _____
Distance _____

Bearing Trees, Reference Objects

Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed:
Monument:


Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
Location filed:
Monument:

Index No. R 13

CASS COUNTY LAND CORNER RECORD

T. 14 R. 28 M. 5TH Coordinates: X _____ Y _____
NE 28 Corner common to sections 21, 22, 27, 28



EXISTING SURVEYS

Original Government Survey

Year surveyed 1874
Original monument POST

Original Evidence Found

Year of search _____ By _____
Monument found _____

Species	Bearing	Trces	Diameter
<u>W. AVE</u>	<u>BIRCH</u>	<u>BIRCH</u>	<u>14"</u>
<u>537E</u>	<u>N 51W</u>	<u>534E</u>	<u>6"</u>
<u>8 LKS</u>	<u>24 LKS</u>	<u>32 LKS</u>	<u>4"</u>

Original Bearing Trees Found

Species	Diameter	Bearing	Distance

ERROR IN RECORDING, IN 1918 (BELOW) FND W. PINE NE

Subsequent Corner Restoration

Year surveyed 1918 By GLO
Location filed SECRETARY OF STATE
Monument FND RAILROAD IRON & GOVT BT: 26" N. PINE
STUMP N 37E 8 LKS SET 2 X 36" I.D. W/ BRASS CAP

Evidence of Subsequent Corner Restoration

Year of search 1971 By William Okerman
found GLO monument in good condition

TWIN ROW
521 / 522
528 / 527

Species	Bearing	Trces	Reference Objects
<u>W. OAK</u>	<u>R. OAK</u>	<u>J. PINE</u>	<u>1918</u>
<u>7"</u>	<u>18"</u>	<u>8"</u>	<u>W. OAK</u>
<u>N 34E</u>	<u>S 24 1/2 E</u>	<u>S 44 1/2 W</u>	<u>N 82 1/4 W</u>
<u>57 LKS</u>	<u>178 LKS</u>	<u>27 LKS</u>	<u>226 LKS</u>

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
<u>W. OAK</u>	<u>8"</u>	<u>N 83 W</u>	<u>32.80'</u>
<u>Elm</u>	<u>7"</u>	<u>S 31 E</u>	<u>69.80'</u>
<u>W. OAK</u>	<u>9"</u>	<u>S 72 W</u>	<u>41.50'</u>
<u>W. OAK</u>	<u>13"</u>	<u>N 30 E</u>	<u>38.00'</u>

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
PLAT - RAMBLING ACRES
R. F. SCHNEIDER 1974
CERTIFICATE - BILL OKERMAN - 1971

Remonumentation certificate prepared _____

By _____

Filed at _____

Date _____