



T. 141 R. 28 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
NE 25 Corner common to sections 24, 25 AND 19, 30-141-27

EXISTING SURVEYS

Original Government Survey

Year surveyed 1873  
 Original monument POST

Bearing Trees  
 Species W. PINE N. PINE  
 Diameter 30" 20"  
 Bearing S30W S10E  
 Distance 47 LKS 46 LKS

Original Evidence Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
 Monument found \_\_\_\_\_

Original Bearing Trees Found

Species \_\_\_\_\_  
 Diameter \_\_\_\_\_  
 Bearing \_\_\_\_\_  
 Distance \_\_\_\_\_

Subsequent Corner Restoration

Year surveyed 1913 By JOHN CURD  
 Location filed COUNTY SURVEY RECORD BOOK "A" P 564-567  
 Monument SET 3X3X3/8" SPRUCE STAKE  
1915, N. D. GORMAN BOOK "B" P. 570-573 FND POST  
AND AN IRON, ALSO OLD GOVT @.TS: 30' W. PINE  
S17-32E 31.02', 30' N. PINE S26-05W 30.36'  
also on microfilm roll 115 BR. 907. 26  
 Bearing Trees, Reference Objects  
 Species PINE STUMP OAK STUB  
 Diameter \_\_\_\_\_ 5"  
 Bearing S20-30E N20E  
 Distance 65.30' 43.65'

Evidence of Subsequent Corner Restoration

Year of search 1919 By GLD  
 FILED AT: SECRETARY OF STATE. FND 2" I.P.  
 AND GOVT B.TS: PINESTUB 25" S75W 47 LKS, 25"  
 PINE S10E 46 LKS SET 2X3/8" I.P. W/BRASS CAP  
 SET IN 1918 T141N  
 R28W R27W  
 524 | 519  
 525 | 530  
 1718  
 Bearing Trees, Reference Objects  
 N. PINE N. PINE W. OAK  
 14" 12" 6"  
 N3E S60-30E N23W  
 325 LKS 164 LKS 473 LKS

Subsequent Corner Restoration

Year surveyed 1922 By J. H. FLYNN  
 Location filed COUNTY BOOK "D" P 76  
 Monument FND GOVT IRON CORNER

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
 Certificate - Roger Mustonen - 1988  
 DOC # 302194  
 Fnd brass cap monument and 1973 USFS BT'S  
 8" Birch S 57 1/2 E 41.80'  
 5" W. Oak S34 W 19.30'  
 7" W. oak S78W 27.34'  
 8" Birch N57W 66.83'