


Index No. F 9

CASS COUNTY LAND CORNER RECORD

T. 141 R. 29 M. 57A Coordinates: X _____ Y _____
N¹¹⁶ Corner common to sections 8, 9



O = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1918
Original monument 1x36" l.p. w/BRASSCAP
N¹¹⁶
S81S9
1918

Original Evidence Found

Year of search _____ By _____
Monument found _____

Bearing Trees
Species R. OAK AsPLAR
Diameter 15" 10"
Bearing S16-45 E S86-30W
Distance 203 LKS 47 LKS

Original Bearing Trees Found

Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration

Year surveyed 1999 By HAROLD CUAD
Location filed COUNTY BOOK "D" P360
Monument END LIM.

Evidence of Subsequent Corner Restoration

Year of search 1981, 1986 By Ken Whitehorn - USFS
End 6LO monument in pieces, set proportionally
a 8" x 24" galv. l.p. w/brass cap.

Bearing Trees, Reference Objects

Species W. BIRCH W. BIRCH
Diameter 5" 6"
Bearing S54-22E S34-36W
Distance 52.73' 65.80'

Bearing Trees, Reference Objects

W. oak Tele. pole W. oak N. Pipe
8" 8" 13"
N73°E S60°E S67°W N79°W
103.80' 69.77' 101.80' 42.03'
SE Cor. Home NW 77.25'

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
Certificate - Ken Whitehorn USFS 1986
Doc # 290144
12/1/99 - R. KOJANEN, TWP. BOARD, CHIEF DEPT SHERIFF
ALL 1981/1986 WITNESSES IN GOOD CONDITION
MAG. READING 15 11'± WEST OF S GRAVEL ROAD
AND 13'± EAST OF STOP SIGN POST

Remonumentation certificate prepared _____

By _____

Filed at _____

Date _____