


Index No. A 23

CASS COUNTY LAND CORNER RECORD

T. 141 R. 30 M. 5TH Coordinates: X _____ Y _____
N1/4 Corner common to sections 1 AND 36-142-30 W.C.



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1873
Original monument W.C. Post

Original Evidence Found

Year of search _____ By _____
Monument found _____

Species	Bearing	Traces
<u>Y. Pine</u>	<u>Y. Pine</u>	
Diameter <u>12"</u>	<u>25"</u>	
Bearing <u>N35 W</u>	<u>S88 1/2 W</u>	
Distance <u>33 LKS</u>	<u>154 LKS</u>	

Species	Bearing	Traces
_____	_____	_____
Diameter _____	_____	_____
Bearing _____	_____	_____
Distance _____	_____	_____

Subsequent Corner Restoration

Year surveyed 1917 By GLD
Location filed Sec. of State
Monument End stump of NW BIT W.C. do not reset w.c.
Sect 14 Cor. 1x36" i.p. w/ brass cap Hy 536
51
1917

Evidence of Subsequent Corner Restoration

Year of search 1981 By Walter Curo
Found 1" x 3/8" brass cap monument
in open bog 3" above surface.

Species	Bearing	Reference Objects
<u>J. Pine</u>	<u>R. Oak</u>	
Diameter <u>10"</u>	<u>8"</u>	
Bearing <u>N78 1/2 E</u>	<u>S32 E</u>	
Distance <u>343 LKS</u>	<u>323 LKS</u>	

Bearing Trees, Reference Objects

Species	Bearing	Reference Objects
<u>Red Oak</u>	<u>W. Oak</u>	
Diameter <u>6"</u>	<u>8"</u>	
Bearing <u>N 84° 30' E</u>	<u>S 75 E</u>	
Distance <u>165.24'</u>	<u>212.94'</u>	

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
CERTIFICATE - WALT CURO - 1981
Doc. # 262627

Remonumentation certificate prepared _____
Filed at _____

By _____
Date _____