


T. 141 R. 30 M. 5TH Coordinates: X _____ Y _____
NE 6 Corner common to sections 5, 6 AND 31, 32 - 142-30



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1873
Original monument POST

Original Evidence Found

Year of search _____ By _____
Monument found _____

Species	Bearing	Trass	Distance
<u>POPLAR</u>	<u>S07°12'W</u>	<u>POPLAR</u>	<u>25 LKS</u>
<u>SOFT MAPLE</u>	<u>8"</u>	<u>POPLAR</u>	<u>12"</u>
<u>POPLAR</u>	<u>N35°12'W</u>	<u>POPLAR</u>	<u>26 LKS</u>
<u>POPLAR</u>	<u>56°7'W</u>	<u>POPLAR</u>	<u>25 LKS</u>
<u>POPLAR</u>	<u>N48°E</u>	<u>POPLAR</u>	<u>25 LKS</u>
<u>POPLAR</u>	<u>12°12'W</u>	<u>POPLAR</u>	<u>25 LKS</u>
<u>POPLAR</u>	<u>50°42'E</u>	<u>POPLAR</u>	<u>25 LKS</u>

Original Bearing Trees Found

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1911 By A.W. MOULSTER
Location filed COUNTY SURVEY RECORD BOOK "A" P478-479
Monument FIND STATE IN PLACE SET FROM OLD GOVT
B.T. STUMPS: 5" POPLAR S37-08W 20', 10" POPLAR S41-57
E 69', 6" POPLAR N66-43E 27.60', 20" W. PINE STUMP
N77-31W 71.60'

Evidence of Subsequent Corner Restoration

Year of search 1975 By MILLO STEFAN
PLAT OF SURVEY "E-73" CORNER RESTORED IN 1975
BY R.F. SCHNEIDER FROM REMAINING G.L.O.
REFERENCE TIES.

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Bearing Trees, Reference Objects

Sept. 1911, Tax rd order shows no survey

A-5

Subsequent Corner Restoration

Year surveyed 1919 By GLO
Location filed Sec. of State
Monument End 2" lib. alongside - Sxt 2x36"
lib. w/ brass cap. T142N R30W
TIES: S31 / S32
R. oak 14" N39E 166 LKS 56 / 55
W. oak 4" S9E 139 LKS T141 N
W. oak 5" S68 1/2 W 76 LKS 1917

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
PLAT - PLAT OF SURVEY
R.F. SCHNEIDER 1975

1939 - Co Hwy Dept - (ORD #13 - (on 16um Rd)

Found corner
SW corner schoolhouse - NE 109.4'
SE ✓ NE 125.8'

1984 - T. Freeman's USFS End Co. Cust. iron set by RFS
in 1975: remains of 1919 B.T.S.: Rotted w. oak stp
S9E 91.7', Rotted w. oak stp: bag S69W 50.2'

New ties by USFS:
7" w. oak S2°E 75.35' } 1975 RFS
12" w. oak N73W 56.60' } ties
10" w. oak S32E 77.00' } new
7" w. oak S72W 53.20' } ties

Remonumentation certificate prepared _____

By _____

Filed at _____

Date _____