


Index No. A 7

CASS COUNTY LAND CORNER RECORD

T. 141 R. 30 M. 5TH Coordinates: X Y
N 1/4 5 Corner common to sections 5 and 32-142-30



EXISTING SURVEYS

Original Government Survey

Year surveyed 1873

Original monument lost

Bearing Trees

Species SOFT MAPLE

Diameter 7"

Bearing N30E

Distance 56 LKS

Original Evidence Found

Year of search By

Monument found

Original Bearing Trees Found

Species

Diameter

Bearing

Distance

Subsequent Corner Restoration

Year surveyed 1911 By A.W. Mowster

Location filed County Survey Record Book "A" P 478-479

Monument Set PROPORTIONALLY

also on microfilm - Roll 105 BK 49 P. 12

Evidence of Subsequent Corner Restoration

Year of search 1975 By MILD STEFAN

PLAT OF SURVEY "E-73" R.F. SCHNEIDER ESTABLISHED

A CASS COUNTY SURVEY MONUMENT FROM REMAINING

GLD REFERENCE TIES.

Bearing Trees, Reference Objects

Species N. PINE STAMP

Diameter 14"

Bearing N59-51W

Distance 13'

Bearing Trees, Reference Objects

Subsequent Corner Restoration

Year surveyed 1919 By GLD

Location filed SEC. OF STATE

Monument Set 1x 3/8" IR. w/ brass cap proportionally

TIES:

W. oak 8" S83 3/4 W 143 LKS 1/4 532

SW corner Turtle Lake Schoolhouse 1917

N 45 3/4 E 166 LKS

Evidence of Subsequent Corner Restoration Found

Year of search By

PLAT - MAKINAWK SHORES

R.F. SCHNEIDER 1974

PLAT - PLAT OF SURVEY

R.F. SCHNEIDER 1975

1999 - Landecker + Assoc.

Cert. of Survey shows that a

CIM ~~was~~ found as corner

1999 - CCSO - find. CIM - located 3.8' W &

13 and E of E/W Twp. Rd. 24.

REF. TIES:

*6" Aspen S65°W 120.81'

*8" P. Oak N40°W 81.14'

*12" P. Oak S38°E 92.02'

SW COR. OF

TOWN HALL BLDG. FOUNDATION - N 57°E 101.56'

* denotes dist. pulled to dbl. hd. nail

Remonumentation certificate prepared By

Filed at Date